

## INDUSTRIAL COMPONENT DATA

# G7L-2A-T 200/240VAC G7L 5086D G7L2AT200240AC OMRON DPST-NA 25A Faston clamp And

Brand: OMRON | Manufacturer Part Number: G7L-2A-T 200/240VAC



|                 |                     |
|-----------------|---------------------|
| Manufacturer    | OMRON               |
| MPN / Reference | G7L-2A-T 200/240VAC |
| Catalog number  | G7L2AT200240AC      |
| Category        | Switching relay     |
| Minimum order   | 20 Pcs              |
| Document ID     | EO-A0E68FDFE9       |
| Generated       | 2026-08-04          |

## Product Overview

DPST-NA 25A Faston clamp And

DPST-NA 25A Faston E Clamp

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path OMRON &gt; Industrial Relays &gt; G7 Power

## Additional Product Information

FeaturesMulti-pole power relay

A high-capacity, high-dielectric-strength relay compatible with momentary voltage drops. G7L is equipped with a double-break mechanism and a test button (excluding -P models).

SPST-NO or DPST-NO contact types

Quick connect, PCB or screw terminals

20, 25 or 30A rated load

Compatible with momentary voltage drops

Wide range of applications with 100 or 200V coils

Ordering information

Contact form

Mounting

Terminals

Order code1

(\_\_\_ = Coil Voltage + AC/DC)

Common Coil Voltages2

PCB

DIN-rail front connecting socket

DIN Rail adaptor

Flange (screw)

E-bracket mounting

PCB

Quick-connect

Screw

DC

AC

SPST-NO

no

yes

yes

no

yes

no

yes

no

G7L-1A-T\_\_\_\_

24

100/120, 200/240

DPST-NO

G7L-2A-T\_\_\_\_

12, 24

24, 100/120, 200/240

SPST-NO

no

no

yes

no

G7L-1A-TUB\_\_\_\_

—

100/120, 200/240

DPST-NO

G7L-2A-TUB\_\_\_\_

24

24, 200/240

no

yes

G7L-2A-BUB\_\_\_\_

—

200/240

yes

no

yes

no

G7L-2A-P\_\_\_\_

24

—

Accessories

For type

Order code

DIN-rail front connecting socket

DIN Rail adaptor

E-Bracket mounting

Coverplate electric shock protection

G7L Screw terminal type

—

P7LF-D

R99-07G7L

P7LF-C

G7L Quick Connect type

P7LF-06

P7LF-D

R99-07G7L

—

Specifications

Coil Ratings

Rated voltage

Rated current

Coil resistance

Must operate voltage

Must release voltage

Max. voltage

Power consumption (approx.)

AC (~)

12 V

142 mA

—

75% max.of rated voltage

15% min. of rated voltage

110% of rated voltage

1.7 to 2.5 VA (60 Hz)

24 V

71 mA

—

50 V

34 mA

—

100 to 120 V

17.0 to 20.4 mA

—

74 V  
18 V  
132 V  
200 to 240 V  
8.5 to 1...

### REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OMRON / G7L-2A-T 200/240VAC with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

#### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.