


INDUSTRIAL COMPONENT DATA

J75KN-P-1039 J75K9000A J75KNP1039 OMRON Adapter to pressure to mount the J7KNU rail DIN 35 mm

Brand: OMRON | Manufacturer Part Number: J75KN-P-1039



Manufacturer	OMRON
MPN / Reference	J75KN-P-1039
Catalog number	J75KNP1039
Category	Accessories/spare parts for low-voltage switch technology
Minimum order	10 Pcs
Document ID	EO-6EF31680E9
Generated	2026-08-05

Product Overview

Adapter to pressure to mount the J7KNU rail DIN 35 mm

Snap-on adapter to mount J7KNU on DIN rail 35 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OMRON > Low Voltage Switchgear > J7KN Contactors

Additional Product Information

AC and DC operated

Integrated auxiliary contact

Available as motor contactor and contactor relay

>3 mm contact clearance acc. to IEC 60335-1 for safety applications

Reversing contactor with mechanical interlock

Mirror contacts (NC) acc. to IEC 60947-4-1 for safety applications

J7KNU is designed to fit 15 mm DIN rails, but J75KN snap-on adapter make it suitable also for the standard 35 mm DIN rail

Specifications & ordering info

Ordering information

Micro motor contactors

AC operated

Type

Ratings

Rated current

Main Contacts

Built-in Aux. contacts¹

Order code

AC2, AC3

AC1

NO

NC

NO

NC

Coil voltage², VAC

replace___with:

380 V

400 V

415 V

kW

660 V

690 V

kW

440 V

A

3 pole, with screw terminals

2.2

—

12

3

—

1

—

J7KNU-05-10-_____

24

48

90

110

180

230

2.2

—

12

3

—

—

1

J7KNU-05-01-_____

24

48

90

110

180
230
4 pole, with screw terminals
2.2
—
12
4
—
—
—
J7KNU-05-40-_____
24
48
90
110
180
230
Reversing, mechanical interlocked
2.2
—
12
3 × 2
—
—
1 × 2
J7KNU-05-01R-_____
24
48
90
110
180
230
DC operated
Type
Ratings
Rated current
Main Contacts
Built-in Aux. contacts3
Order code
AC2, AC3
AC1
NO
NC
NO
NC
Coil voltage, VDC
replace___with:

380 V

400 V

415 V

kW

660 V

690 V

kW

440 V

A

3 pole, with screw terminals

2.2

—

12

3

—

1

—

J7KNU-05-10-____D

24

48

60

110

2.2

—

12

3

—

—

1

J7KNU-05-01-____D

24

48

60

110

4 pole, with screw terminals

2.2

—

12

4

—

—

—

J7KNU-05-40-____D

24

48

60

110

Reversing, mechanical interlocked

2.2

—

12

3 × 2

—

—

1 × 2

J7KNU-05-01R-____D

24

48

60

110

Micro contactor relays....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OMRON / J75KN-P-1039 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.