

INDUSTRIAL COMPONENT DATA

K8DT-AW2TD K8DT0023H K8DTAW2TD OMRON Single phase Current Max and Min 0.1-5 transistor 24V AC/DC 17.5 mm Pus..

Brand: OMRON | Manufacturer Part Number: K8DT-AW2TD



Manufacturer	OMRON
MPN / Reference	K8DT-AW2TD
Catalog number	K8DTAW2TD
Category	Current monitoring relay
Minimum order	1 Pcs
Document ID	EO-E17086D6E1
Generated	2026-08-04

Product Overview

Single phase Current Max and Min 0.1-5 transistor 24V AC/DC 17.5 mm Push-in+
Monitoring relay 17.5mm wide, Single phase over and under current 0.1 to 5 A AC/ DC, 1 x Transistor, 24 V AC/DC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OMRON > Monitoring Relays > K8DT

Additional Product Information

FunctionsOver/under currentInstallation typeDIN railTerminal typePush-inSize17.5 mmSetting range0.1 to 1 A AC/DC, 0.5 to 5 A AC/DCSupply voltage AC20.4-26.4 VSupply voltage DC20.4-26.4 VOutput typeTransistorContact descriptionOpen collectorBody colorBlackExternal current transformer
ETIM for 669516 Relays (EC001440)
Feature Name
Feature Value
Type of electric connection (EF003961)
Spring clamp connection
Voltage type (supply voltage) (EF002991)
AC/DC
Three-phase under current possible (EF003406)
No

Function DC-current hysteresis (EF003411)

Yes

Single-phase under current possible (EF003405)

Yes

External power supply required (EF003292)

Yes

Contains function DC-voltage overcurrent (EF003410)

Yes

With detachable clamps (EF003340)

No

External current transformer (EF001923)

No

Single-phase overcurrent possible (EF003407)

Yes

Three-phase overcurrent possible (EF003408)

No

Contains function DC-voltage under current (EF003409)

Yes

Single-phase hysteresis possible (EF003394)

Yes

Three-phase hysteresis possible (EF003395)

No

Number of contacts as change-over contact (EF008257)

0

Number of contacts as normally open contact (EF008256)

1

Min. adjustable delay-on energization time (EF008190)

0.1 s

Max. permitted delay-on energization time (EF008189)

30 s

Min. adjustable off-delay time (EF008192)

0.25 s

Width (EF000008)

17.5 mm

Number of contacts as normally closed contact (EF008255)

0

Height (EF000040)

90 mm

Rated switch current (EF006706)

5 A

Max. permitted off-delay time (EF008191)

0.25...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OMRON / K8DT-AW2TD with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.