

INDUSTRIAL COMPONENT DATA

D4B-4A17N D4BN4020R D4B4A17N OMRON Metallic DPDB-2NC adjustable Rod M20

Brand: OMRON | Manufacturer Part Number: D4B-4A17N



Manufacturer	OMRON
MPN / Reference	D4B-4A17N
Catalog number	D4B4A17N
Category	End switch
Minimum order	1 Pcs
Document ID	EO-9B96F44896
Generated	2026-08-01

Product Overview

Metallic DPDB-2NC adjustable Rod M20

Limit switch, D4B, M20, DPDB 2-NC (slow-action), adjustable rod lever

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OMRON > Safety > D4B

Additional Product Information

Material housingAluminiumActuator typeAdjustable rod leverConnection methodTerminal blockConduit sizeM20Cable entry directionBottomNumber of contacts, normally-open0Number of contacts, normally-closed2Make before breakSwitch actionSlow actionDirect opening mechanism

ETIM for 134613 Sensors (EC000030)

Feature Name

Feature Value

Explosion safety category for dust (EF003998)

None

Construction type housing (EF004008)

Cuboid

Degree of protection (NEMA) (EF011959)

Other

Coating housing (EF001601)

Other

Degree of protection (IP) (EF005474)

IP67

Alignment of the control element (EF008793)

Other

Type of control element (EF006976)

Other

Type of interface for safety communication (EF003956)

None

Type of electric connection (EF003961)

Plug-in connection others

Type of interface (EF006977)

None

Switching function (EF000189)

Slow-action switch

Housing material (EF001596)

Metal

Explosion safety category for gas (EF003997)

None

Switching function latching (EF007447)

No

With status indication (EF001602)

No

Suitable for safety functions (EF001597)

No

Forced opening (EF006694)

Yes

Output electronic (EF006987)

No

Number of contacts as change-over contact (EF008257)

0

Number of contacts as normally open contact (EF008256)

0

Rated operation current I_e at AC-15, 230 V (EF001385)

10 A

Rated operation current I_e at DC-13, 125 V (EF007085)

0.8 A

Number of safety auxiliary contacts (EF006940)

0

Rated operation current I_e at DC-13, 24 V (EF007087)

6 A

Rated operation current I_e at DC-13, 230 V (EF00138...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OMRON / D4B-4A17N with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.