

INDUSTRIAL COMPONENT DATA

D4E-1G20N D4EN0015A D4E1G20N OMRON Lever roller SPDT 5A Sealed

Brand: OMRON | Manufacturer Part Number: D4E-1G20N



Manufacturer	OMRON
MPN / Reference	D4E-1G20N
Catalog number	D4E1G20N
Category	End switch
Minimum order	10 Pcs
Document ID	EO-7CBFA8DE84
Generated	2026-08-02

Product Overview

Lever roller SPDT 5A Sealed

Limit switch, slim sealed, screw terminal, general purpose, roller lever

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OMRON > Industrial Limit switches / Pushbuttons > Other

Additional Product Information

Material housingZincDegree of protection (IP)IP67Actuator typeRoller leverConnection methodTerminal blockCable entry directionRightNumber of contacts, normally-open0Number of contacts, normally-closed0Number of contacts, change-over1Make before breakSwitch actionSnap actionLoad typeStandard loadWith status indication

ETIM for 133974 Sensors (EC000030)

Feature Name

Feature Value

Explosion safety category for dust (EF003998)

None

Construction type housing (EF004008)

Cuboid

Degree of protection (NEMA) (EF011959)

Other

Coating housing (EF001601)

Other

Degree of protection (IP) (EF005474)

IP67

Alignment of the control element (EF008793)

Other

Type of control element (EF006976)

Roller lever

Type of interface for safety communication (EF003956)

None

Type of electric connection (EF003961)

Other

Type of interface (EF006977)

None

Switching function (EF000189)

Other

Housing material (EF001596)

Metal

Explosion safety category for gas (EF003997)

None

Switching function latching (EF007447)

No

With status indication (EF001602)

No

Suitable for safety functions (EF001597)

No

Forced opening (EF006694)

No

Output electronic (EF006987)

No

Number of contacts as change-over contact (EF008257)

1

Number of contacts as normally open contact (EF008256)

0

Rated operation current I_e at AC-15, 230 V (EF001385)

3 A

Rated operation current I_e at DC-13, 125 V (EF007085)

0.05 A

Number of safety auxiliary contacts (EF006940)

0

Rated operation current I_e at DC-13, 24 V (EF007087)

1.5 A

Rated operation current....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OMRON / D4E-1G20N with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.