

INDUSTRIAL COMPONENT DATA

MKS1XTIN-10 230VAC 367819 MKS1XTIN10AC230.1 OMRON SPST-NA Pushbutton test Indic. Mechanical

Brand: OMRON | Manufacturer Part Number: MKS1XTIN-10 230VAC



Manufacturer	OMRON
MPN / Reference	MKS1XTIN-10 230VAC
Catalog number	MKS1XTIN10AC230.1
Category	Switching relay
Minimum order	1 Pcs
Document ID	EO-9F76555821
Generated	2026-08-03

Product Overview

SPST-NA Pushbutton test Indic. Mechanical

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OMRON > Industrial Relays > MK-I/-S

Additional Product Information

FeaturesExceptionally reliable general-purpose relay

The MK(S) series has proven to be exceptionally reliable since its introduction almost 50 years ago. In order to provide the same easy testing as our other relay families, the MK-S is equipped with a lockable test button offering the same function/operation as the MY(S) and G2R(S) families.

8-pin DPDT and 11-pin 3PDT contact types

Switching current up to 10 A

Lockable test button for easy testing

Temperature rating from -40C up to 60C

Ordering information

Contact form

Mechanical indicator & lockable test button

LED indicator

Diode

Order code1

(____ = coil voltage + AC/DC)

Common coil voltages2

DC

AC

DPDT (2-pole)

yes

no

no

MKS2PI

12, 24, 110

24, 110, 230

yes

MKS2PIN

24

24, 230

3PDT (3-pole)

no

MKS3PI-5

12, 24, 48, 110

12, 24, 110, 230

yes

MKS3PI-D-5

24

N/A

yes

no

MKS3PIN-5

12, 24

24, 110, 230

yes

MKS3PIN-D-5

24

N/A

Sockets & accessories

For type

Order code

DIN rail

Screw

Box clamp

Socket

Clip (set= 2 pcs.)

Socket

MKS2

PF083A-E

PFC-A1

-

PF083A-D

MKS3

PF113A-E
PFC-A1
PF113A-N
PF113A-D
Specifications
Coil ratings
Rated voltage
Must operate voltage
Must release voltage
Max. voltage
Power consumption (approx.)
% of rated voltage
AC
6 V, 12 V, 24 V, 100 V, 110 V, 120 V, 200 V, 220 V, 230 V, 240 V
80% max.
30% min.
110%
2.3 VA (60 Hz)
2.7 VA (50 Hz)
DC
6 V, 12 V, 24 V, 48 V, 100 V, 110 V
15% min.
1.4 W
Contact ratings
Load
2- or 3-pole
Resistive load
($\cos\phi = 1$)
Inductive load
($\cos\phi = 0.4$; $L/R = 7$)
Contact material
AgSnIn
Rated Io...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OMRON / MKS1XTIN-10 230VAC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.