

## INDUSTRIAL COMPONENT DATA

## J7MN-3P-6 J7MN9061C J7MN3P6 OMRON 4 6 / 2.2 KW Tilting

Brand: OMRON | Manufacturer Part Number: J7MN-3P-6



|                 |                                  |
|-----------------|----------------------------------|
| Manufacturer    | OMRON                            |
| MPN / Reference | J7MN-3P-6                        |
| Catalog number  | J7MN3P6                          |
| Category        | Motor protection circuit-breaker |
| Minimum order   | 1 Pcs                            |
| Document ID     | EO-238BEC4653                    |
| Generated       | 2026-08-01                       |

## Product Overview

4 - 6 / 2.2 KW Tilting

Motor-protective circuit breaker, switch type, 3-pole, 4-6 A

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification &amp; Catalog Path

Catalog path OMRON &gt; Low Voltage Switchgear &gt; J7MN Motor Protector

## Additional Product Information

Rated power AC2, AC3 at 400 V [kW]2.2 kW Suitable for motors 3 ~ 400 V [kW]2.2 kW Rated current [A]6 A Setting range thermal overload release current [A]4-6 A Setting range instantaneous short-circuit release current [A]78-78 A Short-circuit breaking capacity at 3 ~ 400 V [kA]100 kA Terminal type Screw Product Width (unpacked)45 mm Product Height (unpacked)98 mm Product Depth (unpacked)75 mm Control type Switch type

ETIM for 234283 Low-voltage industrial controls and switchgear (EC000074)

Feature Name

Feature Value

Degree of protection (IP) (EF005474)

IP20

Type of control element (EF006976)

Rocker lever

Device construction (EF008240)

Complete device in housing

Type of electrical connection of main circuit (EF006819)

Screw connection

Switch off technique (EF007007)  
Thermomagnetic  
Phase failure sensitive (EF007400)  
Yes  
With integrated under voltage release (EF001390)  
No  
With integrated auxiliary switch (EF001387)  
No  
Rated permanent current  $I_u$  (EF001389)  
6 A  
Rated short-circuit breaking capacity  $I_{cu}$  at 400 V, AC (EF007049)  
100 kA  
Width (EF000008)  
45 mm  
Rated operation power at AC-3, 400 V (EF001364)  
2.2 kW  
Height (EF000040)  
98 mm  
Number of poles (EF001391)  
3  
Depth (EF000049)  
75 mm  
Rated operation power at AC-3, 230 V (EF007025)  
2.2 kW  
Overload release current setting (EF002336)  
4 A  
Adjustment range undelayed short-circuit release (EF007131)  
78 A  
Rated operating voltage (EF001435)  
400 V

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OMRON / J7MN-3P-6 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.