

INDUSTRIAL COMPONENT DATA

J7MN-6R-40 J7MN9087G J7MN6R40 OMRON 28 40 A / 18,5 KW Rotary

Brand: OMRON | Manufacturer Part Number: J7MN-6R-40



Manufacturer	OMRON
MPN / Reference	J7MN-6R-40
Catalog number	J7MN6R40
Category	Motor protection circuit-breaker
Minimum order	1 Pcs
Document ID	EO-3014151BAE
Generated	2026-08-01

Product Overview

28 - 40 A / 18,5 KW Rotary

Motor-protective circuit breaker, rotary type, 3-pole, 28-40 A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **OMRON > Low Voltage Switchgear > J7MN Motor Protector**

Additional Product Information

Rated power AC2, AC3 at 400 V [kW]18.5 kWSuitable for motors 3 ~ 400 V [kW]18.5 kWRated current [A]40 ASetting range thermal overload release current [A]28-40 ASetting range instantaneous short-circuit release current [A]520-520 AShort-circuit breaking capacity at 3 ~ 400 V [kA]50 kATerminal typeScrewProduct Width (unpacked)55 mmProduct Height (unpacked)140 mmProduct Depth (unpacked)144 mmControl typeRotary type
ETIM for 234309 Low-voltage industrial controls and switchgear (EC000074)

Feature Name

Feature Value

Degree of protection (IP) (EF005474)

IP20

Type of control element (EF006976)

Rotating button

Device construction (EF008240)

Complete device in housing

Type of electrical connection of main circuit (EF006819)

Screw connection
Switch off technique (EF007007)
Thermomagnetic
Phase failure sensitive (EF007400)
Yes
With integrated under voltage release (EF001390)
No
With integrated auxiliary switch (EF001387)
No
Rated permanent current I_u (EF001389)
40 A
Rated short-circuit breaking capacity I_{cu} at 400 V, AC (EF007049)
50 kA
Width (EF000008)
55 mm
Rated operation power at AC-3, 400 V (EF001364)
18.5 kW
Height (EF000040)
140 mm
Number of poles (EF001391)
3
Depth (EF000049)
144 mm
Rated operation power at AC-3, 230 V (EF007025)
18.5 kW
Overload release current setting (EF002336)
28 A
Adjustment range undelayed short-circuit release (EF007131)
520 A
Rated operating voltage (EF001435)
400 V

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OMRON / J7MN-6R-40 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.