

## INDUSTRIAL COMPONENT DATA

# MY4IN-D2-GS-R DC24 MY4 5748F MY4IND2GSRDC24BYOMZ OMRON Relay, plug-in, 14-pin, 4PDT, 3 A, mechanical and LED..

Brand: OMRON | Manufacturer Part Number: MY4IN-D2-GS-R DC24



|                 |                     |
|-----------------|---------------------|
| Manufacturer    | OMRON               |
| MPN / Reference | MY4IN-D2-GS-R DC24  |
| Catalog number  | MY4IND2GSRDC24BYOMZ |
| Category        | Switching relay     |
| Minimum order   | 1 Pcs               |
| Document ID     | EO-EFE84F1771       |
| Generated       | 2026-08-06          |

## Product Overview

Relay, plug-in, 14-pin, 4PDT, 3 A, mechanical and LED indicators, coil suppressor, lockable test pushbutton, 24 VDC  
Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical & LED indicators, Coil Surge Absorption, lockable push test button, 24 VDC

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |       |
|--------------|-------|
| Catalog path | OMRON |
|--------------|-------|

## Additional Product Information

Mounting methodWith plug-in socketUsageGeneral purposePoles4Rated carry current6 ACoil voltage24 VOperation voltageDCContact materialAgContact description4PDTFeaturesDiode, LED, Test button, Transparent case, With mechanical indicatorTerminal typePlug-in, Solder  
ETIM for 720104 Relays (EC001437)  
Feature Name  
Feature Value  
Type of switch contact (EF003358)  
Single contact  
Degree of protection (IP) (EF005474)  
Other  
Drive, polarization (EF003355)  
Polarized

Voltage type for actuating (EF008242)

DC

Type of electric connection (EF003961)

Plug-in connection

Drive, switching attitude (EF003356)

Mono stable

With detachable clamps (EF003340)

No

Complete with socket (EF003359)

No

With LED indication (EF005950)

Yes

With forced-guided contacts (EF003357)

No

Number of contacts as change-over contact (EF008257)

4

Number of contacts as normally open contact (EF008256)

0

Width (EF000008)

21.5 mm

Number of contacts as normally closed contact (EF008255)

0

Height (EF000040)

28 mm

Depth (EF000049)

36 mm

Nominal current (EF000001)

6 A

Rated control supply voltage DC (EF003980)

19.2 V

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OMRON / MY4IN-D2-GS-R DC24 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.