

INDUSTRIAL COMPONENT DATA

F3S-TGR-NLPR-20-10 AA020796D F3STGRNLPR2010 OMRON

Switch Sec. PLe Plast. Long Reed 2NC Cable 10m

Brand: OMRON | Manufacturer Part Number: F3S-TGR-NLPR-20-10



Manufacturer	OMRON
MPN / Reference	F3S-TGR-NLPR-20-10
Catalog number	F3STGRNLPR2010
Category	Position switch with separate actuator
Minimum order	1 Pcs
Document ID	EO-51208C4F99
Generated	2026-08-05

Product Overview

Switch Sec. PLe Plast. Long Reed 2NC Cable 10m

Non-contact door switch, reed, elongated sensor 10m, plastic, 2NC contacts

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OMRON > Safety > Contactless Switches TGR

Additional Product Information

Door switch typeNon-contact, ReedGuard-lockCodingUncodedMaterial housingPolyesterAmbient temperature (operating)-25-80 °CDoor contacts NC2Door contacts NO1LED indicatorConnection methodCableCable length10 mCable exit directionLeftDegree of protection (IP)IP69KOutput typeReed contactShapeRectangularOverall length of sensor88 mmHeight of sensor13 mmWidth of sensor25 mmSwitch without actuator

ETIM for 231386 Sensors (EC002592)

Feature Name

Feature Value

Explosion safety category for dust (EF003998)

None

Construction type housing (EF004008)

Cuboid

Type of switching contact (EF003591)

Other

Degree of protection (NEMA) (EF011959)

Other
Coating housing (EF001601)
Other
Degree of protection (IP) (EF005474)
Other
Type of interface for safety communication (EF003956)
None
Type of electric connection (EF003961)
With cable preassembled
Type of interface (EF006977)
None
Housing material (EF001596)
Plastic
Explosion safety category for gas (EF003997)
None
With status indication (EF001602)
No
Suitable for safety functions (EF001597)
Yes
Forced opening (EF006694)
No
Number of contacts as change-over contact (EF008257)
0
Number of contacts as normally open contact (EF008256)
1
Rated operation current I_e at AC-15, 230 V (EF001385)
1 A
Number of safety auxiliary contacts (EF006940)
0
Rated operation current I_e at DC-13, 24 V (EF007087)
0.2 A
Number of contacts as normally closed contact (EF008255)
2
Width sensor (EF007094)
25 mm
Height of sensor (EF007283)
13 mm
Length of sensor (EF007334)
88....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OMRON / F3S-TGR-NLPR-20-10 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.