

INDUSTRIAL COMPONENT DATA

NX-TS2104 NX020052F NXTS2104 OMRON Unit NX 2 Inputs for Temperature Sensor, K, J, T, E, L, U, N, R, S, WRe5-..

Brand: OMRON | Manufacturer Part Number: NX-TS2104



Manufacturer	OMRON
MPN / Reference	NX-TS2104
Catalog number	NXTS2104
Category	Fieldbus, decentr. periphery - analogue I/O module
Minimum order	1 Pcs
Document ID	EO-F66F56A3AF
Generated	2026-08-03

Product Overview

Unit NX - 2 Inputs for Temperature Sensor, K, J, T, E, L, U, N, R, S, WRe5-26, PLII, resolution 0.001°C max., 60 ms/Unit
NX Unit - 2 Temperature Sensor Inputs, K, J, T, E, L, U, N, R, S, WRe5-26, PLII, resolution 0.001°C max., 60 ms/Unit
2 Thermocouple Inputs, type K, J, T, E, L, U, N, R, S, B, C(W/Re5-26), P(PLII), resolution 0.001°C, 60 ms/Unit, screwless push-in connector, 12 mm wide

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	OMRON > Integrated Automation > Machine I/O NX-series
--------------	---

Additional Product Information

I/O systemNX I/O BusType of moduleAnalog I/ONumber of analog inputs2Temperature input typeB, C (WRe5-26), E, J, K, L, N, P (PLII), R, S, T, ULinear analog input typeNoneResolution of the analog inputs20 BitInput circuit typeDifferentialNumber of analog outputs0Linear analog output typeNoneResolution of the analog outputs0 BitConversion time60 ms/unitSignal processingFree runningIO-Link masterI/O connection typePush-inNumber of I/O connectors1Detachable I/O connectorSuitable for safety functionsSIL according to IEC 61508NoneDegree of protection (IP)IP20Product Height (unpacked)100 mmProduct Width (unpacked)12 mmProduct Depth (unpacked)80 mmProduct Weight (unpacked)70 g
ETIM for 380134 PLC's (EC001596)
Feature Name
Feature Value
Degree of protection (NEMA) (EF011959)
Other

Degree of protection (IP) (EF005474)

IP20

Performance level according to EN ISO 13849-1 (EF007399)

Level a

SIL according to IEC 61508 (EF009889)

None

Voltage type (supply voltage) (EF002991)

DC

Explosion safety category for gas (EF003997)

None

Explosion safety category for dust (EF003998)

None

Type of electric connection (EF003961)

Spring clamp connection

Output, current (EF003212)

No

Radio standard UMTS (EF008525)

No

Input, voltage (EF003205)

No

Input, thermocouple (EF003208)

Yes

Supporting protocol for EtherCAT (EF017564)

Yes

Analogue inputs configurable (EF008518)

Yes

Appendant operation agent (Ex ib) (EF004142)

No

Input, current (EF003204)

No

Supporting protocol for other bus systems (EF003062)

Yes

Analo...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OMRON / NX-TS2104 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.