

INDUSTRIAL COMPONENT DATA

MKS2PI 48VDC MKSN8414E MKS2PIDC48BYOMZ OMRON

DPDT 10A Indic. mechanical Push button-test

Brand: OMRON | Manufacturer Part Number: MKS2PI 48VDC



Manufacturer	OMRON
MPN / Reference	MKS2PI 48VDC
Catalog number	MKS2PIDC48BYOMZ
Category	Switching relay
Minimum order	20 Pcs
Document ID	EO-4DA6E4FF79
Generated	2026-07-27

Product Overview

DPDT 10A Indic. mechanical Push button-test

DPDT 10A Indic. Mechanical Push-Button Test

Relay, plug-in, 8-pin, DPDT, 10 A, mech indicator, test button

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OMRON > Industrial Relays > MK-II-S

Additional Product Information

FeaturesExceptionally reliable general-purpose relay

The MK(S) series has proven to be exceptionally reliable since its introduction almost 50 years ago. In order to provide the same easy testing as our other relay families, the MK-S is equipped with a lockable test button offering the same function/operation as the MY(S) and G2R(S) families.

8-pin DPDT and 11-pin 3PDT contact types

Switching current up to 10 A

Lockable test button for easy testing

Temperature rating from -40C up to 60C

Ordering information

Contact form

Mechanical indicator & lockable test button

LED indicator

Diode

Order code1

(____ = coil voltage + AC/DC)

Common coil voltages2

DC

AC

DPDT (2-pole)

yes

no

no

MKS2PI

12, 24, 110

24, 110, 230

yes

MKS2PIN

24

24, 230

3PDT (3-pole)

no

MKS3PI-5

12, 24, 48, 110

12, 24, 110, 230

yes

MKS3PI-D-5

24

N/A

yes

no

MKS3PIN-5

12, 24

24, 110, 230

yes

MKS3PIN-D-5

24

N/A

Sockets & accessories

For type

Order code

DIN rail

Screw

Box clamp

Socket

Clip (set= 2 pcs.)

Socket

MKS2

PF083A-E

PFC-A1

-

PF083A-D

MKS3

PF113A-E

PFC-A1

PF113A-N

PF113A-D

Specifications

Coil ratings

Rated voltage

Must operate voltage

Must release voltage

Max. voltage

Power consumption (approx.)

% of rated voltage

AC

6 V, 12 V, 24 V, 100 V, 110 V, 120 V, 200 V, 220 V, 230 V, 240 V

80% max.

30% min.

110%

2.3 VA (60 Hz)

2.7 VA (50 Hz)

DC

6 V, 12 V, 24 V, 48 V, 100 V, 110 V

15% min.

1.4 W

Contact ratings

Load

2- or 3-pole

Resistive load

(cos ϕ = 1)

Inductive load

(cos ϕ = 0.4; L/R = 7)

Contact material

AgSnIn

Rated lo...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OMRON / MKS2PI 48VDC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.