

INDUSTRIAL COMPONENT DATA

G32A-A60-VD 5-24VDC G32 5006M G32AA60VDDC524BYOMZ OMRON Cartridge power for G3PA-260B-VD

Brand: OMRON | Manufacturer Part Number: G32A-A60-VD 5-24VDC



Manufacturer	OMRON
MPN / Reference	G32A-A60-VD 5-24VDC
Catalog number	G32AA60VDDC524BYOMZ
Category	Solid state relay
Minimum order	1 Pcs
Document ID	EO-EBE7643BB0
Generated	2026-07-31

Product Overview

Cartridge power for G3PA-260B-VD
Replacement cartridge for G3PA-260B SSR, suitable for 'VD' versions only

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OMRON > Solid State Relays > Accessories

Additional Product Information

FeaturesSolid State Relays with exchangeable power cartridge
Optimum design of the heat sink has contributed to the downsizing of this product. The power element cartridges of the G3PA are easily replaceable for easy maintenance. G3PA can be mounted on a DIN-rail or using screws.
20-60 A output current
24-480 VAC output voltages
Applicable with 3-phase loads
Replaceable power element cartridges
Ordering information
Rated output load
Zero cross function
Rated input voltage
Operating voltage range
Input
current impedance

Voltage level

Size in mm

(H×W×D)

Order code

Must operate voltage

Must release voltage

24 to 240 VAC

40 A

Yes

5 to 24 VDC

4 to 30 VDC

7 mA max.

4 VDC max.

1 VDC min.

100×47×100

G3PA-240B-VD DC5-24

60 A

100×110×100

G3PA-260B-VD DC5-24

40 A

24 VAC

19.2 to 26.4 VAC

1.4 k? ±20%

19.2 VAC max.

4.8 VAC min.

100×47×100

G3PA-240B-VD AC24

60 A

100×110×100

G3PA-260B-VD AC24

180 to 400 VAC

20 A

12 to 24 VDC

9.6 to 30 VDC

7 mA max.

9.2 VDC max.

1 VDC min.

100×37×100

G3PA-420B-VD DC12-24

30 A

100×47×100

G3PA-430B-VD DC12-24

200 to 480 VAC

20 A

100×37×100

G3PA-420B-VD-2 DC12-24

30 A

100×47×100
G3PA-430B-VD-2 DC12-24
50 A
100×110×100
G3PA-450B-VD-2 DC12-24
Accessories
Replacement parts: Power device cartridges
Load voltage range
Carry current
Applicable SSR
Order code
19 to 264 VAC
40 A
G3PA-240B-VD DC5-24
G32A-A40-VD DC5-24
G3PA-240B-VD AC24
G32A-A40-VD AC24
60 A
G3PA-260B-VD DC5-24
G32A-A60-VD DC5-24
G3PA-260B-VD AC24
G32A-A60-VD AC24
150 to 440 VAC
20 A
G3PA-420B-VD DC12-24...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OMRON / G32A-A60-VD 5-24VDC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.