

INDUSTRIAL COMPONENT DATA

D4B-4115N D4BN4022E D4B4115N OMRON Metal SPDT-no/NC abrupt Break Roller plunger stainless steel. M20

Brand: OMRON | Manufacturer Part Number: D4B-4115N



Manufacturer	OMRON
MPN / Reference	D4B-4115N
Catalog number	D4B4115N
Category	End switch
Minimum order	1 Pcs
Document ID	EO-C70F99E4A5
Generated	2026-07-29

Product Overview

Metal SPDT-no/NC abrupt Break Roller plunger stainless steel. M20
Limit switch, D4B, M20, 1NC/1NO (snap-action), roller lever (stainless steel)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	OMRON > Safety > D4B
--------------	----------------------

Additional Product Information

Material housingAluminiumActuator typeRoller leverActuator detailMetal rollerConnection methodTerminal blockConduit sizeM20Cable entry directionBottomNumber of contacts, normally-open1Number of contacts, normally-closed1Make before breakSwitch actionSnap actionDirect opening mechanism
ETIM for 370630 Sensors (EC000030)
Feature Name
Feature Value
Explosion safety category for dust (EF003998)
None
Construction type housing (EF004008)
Cuboid
Degree of protection (NEMA) (EF011959)
6P
Coating housing (EF001601)
Other

Degree of protection (IP) (EF005474)

IP67

Alignment of the control element (EF008793)

Roller cam straight

Type of control element (EF006976)

Roller lever

Type of interface for safety communication (EF003956)

None

Type of electric connection (EF003961)

Cable entry metrical

Type of interface (EF006977)

None

Switching function (EF000189)

Quick-break switch

Housing material (EF001596)

Metal

Explosion safety category for gas (EF003997)

None

Switching function latching (EF007447)

No

With status indication (EF001602)

No

Suitable for safety functions (EF001597)

Yes

Forced opening (EF006694)

Yes

Output electronic (EF006987)

No

Number of contacts as change-over contact (EF008257)

0

Number of contacts as normally open contact (EF008256)

1

Rated operation current I_e at AC-15, 230 V (EF001385)

10 A

Rated operation current I_e at DC-13, 125 V (EF007085)

0.8 A

Number of safety auxiliary contacts (EF006940)

0

Rated operation current I_e at DC-13, 24 V (EF007087)

6 A

Rated operation cu...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OMRON / D4B-4115N with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.