

INDUSTRIAL COMPONENT DATA

D4BL-1DRG-A D4BL0024M D4BL1DRGA OMRON Metal 2NC+1NC LED 24vdc Bloqueo solenoid PG13,5

Brand: OMRON | Manufacturer Part Number: D4BL-1DRG-A



Manufacturer	OMRON
MPN / Reference	D4BL-1DRG-A
Catalog number	D4BL1DRGA
Category	Position switch with guard locking
Minimum order	1 Pcs
Document ID	EO-830DCFDAB9
Generated	2026-07-29

Product Overview

Metal 2NC+1NC LED 24vdc Bloqueo solenoid PG13,5

Metallic 2NC+1NC LED 24Vcc Solenoid Lock PG13.5

Safety door-lock switch, PG13.5, 24 VDC solenoid lock, mechanical release, 2NC (slow-action), 1NC (slow-action), LED

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OMRON > Safety > Others

Additional Product Information

ETIM for 134700 Sensors (EC002593)

Feature Name

Feature Value

Explosion safety category for dust (EF003998)

None

Construction type housing (EF004008)

Cuboid

Type of switching contact (EF003591)

Slow-action switch

Degree of protection (NEMA) (EF011959)

Other

Degree of protection (IP) (EF005474)

IP67

Type of interface for safety communication (EF003956)

None

Type of electric connection (EF003961)

Cable entry PG

Type of interface (EF006977)

None

Housing material (EF001596)

Metal

Explosion safety category for gas (EF003997)

None

With status indication (EF001602)

Yes

Suitable for safety functions (EF001597)

Yes

With escape release (EF007172)

Yes

Number of contacts as change-over contact (EF008257)

0

Number of contacts as normally open contact (EF008256)

0

Guard locking force (EF007552)

700 N

Number of safety auxiliary contacts (EF006940)

0

Rated operation current I_e at DC-13, 24 V (EF007087)

0 A

Rated operation current I_e at DC-13, 230 V (EF001386)

0 A

Number of contacts as normally closed contact (EF008255)

3

Rated operation current I_e at AC-15, 125 V (EF007082)

6 A

Width sensor (EF007094)

112 mm

Height of sensor (EF007283)

46.3 mm

Length of sensor (EF007334)

123.5 mm

Ambient temperature during operating (EF007515)

-10 °C

Rated control supply voltage magnet drive DC (EF007070)

20.4 V

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OMRON / D4BL-1DRG-A with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.