

INDUSTRIAL COMPONENT DATA

D4N-4C25 D4N 0288G D4N4C25 OMRON Plastic 2NC/1NO Slow Lever Roller Metal M20

Brand: OMRON | Manufacturer Part Number: D4N-4C25



Manufacturer	OMRON
MPN / Reference	D4N-4C25
Catalog number	D4N4C25
Category	End switch
Minimum order	1 Pcs
Document ID	EO-EDDF13B8E9
Generated	2026-07-29

Product Overview

Plastic 2NC/1NO Slow Lever Roller Metal M20

Limit switch, Roller lever (metal lever, metal roller), 2NC/1NO (slow-action), 2NC/1NO (slow-action), M20 (1-conduit)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OMRON > Safety > D4N

Additional Product Information

Specifications

Material housing Plastic

Actuator type Roller lever

Actuator detail Metal lever, Metal roller

Connection method Terminal block

Conduit size M20

Cable entry direction Bottom

Number of contacts, normally-open 1

Number of contacts, normally-closed 2

Make before break

Switch action Slow action

ETIM for 170364 Sensors (EC000030)

Feature Name

Feature Value

Explosion safety category for dust (EF003998)
None

Construction type housing (EF004008)
Cuboid

Degree of protection (NEMA) (EF011959)
Other

Coating housing (EF001601)
Other

Degree of protection (IP) (EF005474)
IP67

Alignment of the control element (EF008793)
Roller cam straight

Type of control element (EF006976)
Roller lever

Type of interface for safety communication (EF003956)
None

Type of electric connection (EF003961)
Cable entry metrical

Type of interface (EF006977)
None

Switching function (EF000189)
Slow-action switch

Housing material (EF001596)
Plastic

Explosion safety category for gas (EF003997)
None

Switching function latching (EF007447)
No

With status indication (EF001602)
No

Suitable for safety functions (EF001597)
Yes

Forced opening (EF006694)
Yes

Output electronic (EF006987)
No

Number of contacts as change-over contact (EF008257)
0

Number of contacts as normally open contact (EF008256)
1

Rated operation current I_e at AC-15, 230 V (EF001385)
3 A

Rated operation current I_e at DC-13, 125 V (EF007085)
0.55 A

Number of safety auxiliary contacts (EF006940)
0

Rated operation current I_e at DC-13, 230 V (EF0013...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OMRON / D4N-4C25 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.