

INDUSTRIAL COMPONENT DATA

D4SL-N4RDG-D4N D4SL2384D D4SLN4RDGD4N OMRON Lock solenoid 3nc contact forms + 3nc contact forms IP67 M20 LED..

Brand: OMRON | Manufacturer Part Number: D4SL-N4RDG-D4N



Manufacturer	OMRON
MPN / Reference	D4SL-N4RDG-D4N
Catalog number	D4SLN4RDGD4N
Category	Position switch with guard locking
Minimum order	1 Pcs
Document ID	EO-D7783CBFDF
Generated	2026-07-29

Product Overview

Lock solenoid 3nc contact forms + 3nc contact forms IP67 M20 LED Metal Connector special Key

Solenoid Lock 3NC + 3NC IP67 M20 LED Metal Connector Special Key

Door locking switch, M20, 3NC + 3NC, head: metal, 24VDC solenoid lock/mechanical release, LED indicator, special release key, connector

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OMRON > Safety > D4DL/DS/DH/DR/GL/NL/NH/NS

Additional Product Information

ETIM for 377990 Sensors (EC002593)

Feature Name

Feature Value

Explosion safety category for dust (EF003998)

None

Construction type housing (EF004008)

Cuboid

Type of switching contact (EF003591)

Slow-action switch

Degree of protection (NEMA) (EF011959)

4X
Coating housing (EF001601)
Other
Degree of protection (IP) (EF005474)
IP67
Type of interface for safety communication (EF003956)
None
Type of electric connection (EF003961)
Cable entry metrical
Type of interface (EF006977)
None
Housing material (EF001596)
Plastic
Explosion safety category for gas (EF003997)
None
With auxiliary release (EF011964)
Yes
With status indication (EF001602)
Yes
Suitable for safety functions (EF001597)
Yes
With escape release (EF007172)
Yes
Number of contacts as change-over contact (EF008257)
0
Number of contacts as normally open contact (EF008256)
0
Guard locking force (EF007552)
1300 N
Rated operation current I_e at DC-13, 125 V (EF007085)
0.22 A
Number of safety auxiliary contacts (EF006940)
0
Number of contacts as normally closed contact (EF008255)
6
Rated operation current I_e at AC-15, 125 V (EF007082)
1.5 A
Width sensor (EF007094)
39 mm
Height of sensor (EF007283)
39 mm
Length of sensor (EF007334)
155 mm
Ambient temperature during operating (EF007515)
-10 °C
Rated control supply voltage magnet drive DC (EF007070)
20.4 V

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OMRON / D4SL-N4RDG-D4N with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.