


INDUSTRIAL COMPONENT DATA

F3E-IK-S AA020974F F3EIKS OMRON Mounting Kit for fixed installation.

Brand: OMRON | Manufacturer Part Number: F3E-IK-S



Manufacturer	OMRON
MPN / Reference	F3E-IK-S
Catalog number	F3EIKS
Category	Accessories/spare parts for sensor technology
Minimum order	1 Pcs
Document ID	EO-53DC676312
Generated	2026-08-01

Product Overview

Mounting Kit for fixed installation.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	OMRON > Advanced sensors > Accessories Sensors
--------------	--

Additional Product Information

Thin 9 mm shape for easy design-in in elevator constructions
High ambient light immunity
Robust aluminium housing
Fulfills requirements of EN81-70 (1800 mm models) for mounting in elevators
Specifications & ordering info
Ordering information
Sensor type
Detection
area
Pitch
Sensing
distance
Channels
Number of
optical axis

Connection method

Order code1

Potential free output

Through-beam

200 mm

40 mm

5 m

6

16

-

-

5 m

-

F3E-06-T1 5M

¢

-

-

-

F3E-06-T6

1320 mm

120 mm

12

34

-

-

5 m

-

F3E-12-T1 5M

¢

-

-

-

F3E-12-T6

1800 mm

120 mm

16

46

-

-

5 m

-

F3E-16-T1 5M

¢

-

-

-

F3E-16-T6

40 mm

46

136

-

-

5 m

-

F3E-46-T1 5M

¢

-

-

-

F3E-46-T6

Specifications

Item

Through-beam

F3E-06-T_

F3E-12-T_

F3E-16-T_

F3E-46-T_

Number of LEDs

6

12

16

46

Number of optical axes

16

34

46

136

Pitch

40 mm

120 mm

120 mm

40 mm

Vertical detection range

20 to 200 mm

20 to 1320 mm

20 to 1820 mm

Response time

max. 110 ms (signal interruption)

Light source (wave length)

Infrared LED (880 nm)

Power supply voltage

10 to 30 VDC

Ambient temperature

Operation

-20 to 60°C

Storage

-40 to 70°C

EMC conformity/standards

73/23/EWG; 89/336/EWG; 95/16/EG; EN81-1; EN81-2; EN12015; EN12016; EN61000-6-x

Degree of protection

IEC 60529 IP54

Dimensions

400 × 40.7 × 9 mm

1590 × 40.7 × 9 mm

2070 × 40.7 × 9 mm

2000 × 40.7 × 9 mm

Material

Case

Aluminum

1.Light-ON/Dark-ON settable. Common operation is Dark-ON

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OMRON / F3E-IK-S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.