

INDUSTRIAL COMPONENT DATA

J7KNA-AR-22 48VS J7KA9118E J7KNAAR2248VS OMRON Mini contactor relay, 4-pole (2 NO & 2 NC), 10 A, AC1 (up to ..

Brand: OMRON | Manufacturer Part Number: J7KNA-AR-22 48VS



Manufacturer	OMRON
MPN / Reference	J7KNA-AR-22 48VS
Catalog number	J7KNAAR2248VS
Category	Contactor relay
Minimum order	1 Pcs
Document ID	EO-86CF400A8F
Generated	2026-08-01

Product Overview

Mini contactor relay, 4-pole (2 NO & 2 NC), 10 A, AC1 (up to 690 VAC) 48 VDC + diode

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **OMRON > Low Voltage Switchgear > J7KN Contactors**

Additional Product Information

Mirror contacts
 Screw fixing and snap fitting (35mm DIN-rail)
 Rated current = 10A (I-th)
 Suitable for electronic devices (DIN 19240)
 Finger proof (BGV A2)
 Specifications & ordering info
 Ordering information
 Operation
 Contacts
 Distinctive number according to
 DIN EN 50011
 Ratings
 Thermal rated current
 Order code
 Coil voltage1,

replace ____ with:

AC15

230 V

A

400 V

A

NO

NC

I_{th}, A

4-pole, with screw terminals

VAC

VDC

AC

4

0

40 E

3

2

10

J7KNA-AR-40 ____

24

110

230

-

-

3

1

31 E

3

2

10

J7KNA-AR-31 ____

24

110

230

-

-

2

2

22 E

3

2

10

J7KNA-AR-22 ____

24

110

230

-
-
DC solenoid
4
0
40 E
3
2
10
J7KNA-AR-40 ____
-
-
-
24D
110D
3
1
31 E
3
2
10
J7KNA-AR-31 ____
-
-
-
24D
110D
2
2
22 E
3
2
10
J7KNA-AR-22 ____
-
-
-
24D
110D
DC solenoid with diode
4
0
40 E
3
2
10
J7KNA-AR-40 ____

-

-

-

24VS

-

3

1

31 E

3

2

10

J7KNA-AR-31 ____

-

-

-

24VS

-

2

2

22 E

3

2

10

J7KNA-AR-22 ____

-

-

-

24VS

-

Accessories

Contacts

Ratings

Thermal rated current

Order code

AC15

230 V

A

400 V

A

NO

NC

I_{th}, A

1

1

3

2

10

J73KN-A-11

0
2
3
2
10

J73KN-A-02

4
0
3
2
10

J73KN-A-40

2
2
3
2
10

J73KN-A-22

0
4
3
2
10

J73KN-A-04

Specifications

Suffix to contactor type

e.g. J7KNA-09-10-24

Voltage marking at the coil for

Rated control voltage U_s range for

50 Hz

60 Hz

50 Hz

60 Hz

V

V

min. V

max. V

min. V

max. V

24

24

24

22

24

24

24

24

110

110 to 115

120 to 125

110

115

120

125

230

220 to 230

240

220

230

240

250

1.Other coil voltages available on request

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OMRON / J7KNA-AR-22 48VS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.