

INDUSTRIAL COMPONENT DATA

K8AK-AS1 24VAC/DC K8AK0002M K8AKAS124VACDC

OMRON Single phase Current Max or Min 20-500mA 24VAC/DC 1 SPDT

Brand: OMRON | Manufacturer Part Number: K8AK-AS1 24VAC/DC



Manufacturer	OMRON
MPN / Reference	K8AK-AS1 24VAC/DC
Catalog number	K8AKAS124VACDC
Category	Current monitoring relay
Minimum order	1 Pcs
Document ID	EO-37E2370D3F
Generated	2026-08-01

Product Overview

Single phase Current Max or Min 20-500mA 24VAC/DC 1 SPDT

Monitoring relay 22.5mm wide, Single phase over or under current 2 to 500mA AC or DC, One SPDT, 24VAC/DC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OMRON > Monitoring Relays > K8AK

Additional Product Information

Specifications

Functions Current

Installation type DIN rail

Terminal type Screw

Size 22.5 mm

Supply voltage AC 20.4-26.4 V

Supply voltage DC 20.4-26.4 V

Output type Relay

Contact description SPDT

Body color Black

External current transformer

ETIM for 378159 Relays (EC001440)

Feature Name

Feature Value

Type of electric connection (EF003961)

Screw connection

Voltage type (supply voltage) (EF002991)

AC/DC

Three-phase under current possible (EF003406)

No

Function DC-current hysteresis (EF003411)

Yes

Single-phase under current possible (EF003405)

Yes

External power supply required (EF003292)

Yes

Contains function DC-voltage overcurrent (EF003410)

No

With detachable clamps (EF003340)

No

External current transformer (EF001923)

No

Single-phase overcurrent possible (EF003407)

Yes

Three-phase overcurrent possible (EF003408)

No

Contains function DC-voltage under current (EF003409)

No

Single-phase hysteresis possible (EF003394)

Yes

Three-phase hysteresis possible (EF003395)

No

Number of contacts as change-over contact (EF008257)

1

Number of contacts as normally open contact (EF008256)

0

Min. adjustable delay-on energization time (EF008190)

0.1 s

Max. permitted delay-on energization time (EF008189)

30 s

Min. adjustable off-delay time (EF008192)

0.1 s

Width (EF000008)

22.5 mm

Number of contacts as normally closed contact (EF008255)

0

Height (EF000040)

90 mm

Rated switch current (EF006706)

5 A

Max. permitted off-delay time (EF008191)

30 s

Depth (EF000049)

100 mm

Supply voltage AC 50 Hz (EF...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OMRON / K8AK-AS1 24VAC/DC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.