

INDUSTRIAL COMPONENT DATA

K8AK-VW2 100-240VAC K8AK0017H K8AKVW2100240VAC OMRON Single-phase Voltage Max and Min 1-150VAC/DC 100-240VAC..

Brand: OMRON | Manufacturer Part Number: K8AK-VW2 100-240VAC



Manufacturer	OMRON
MPN / Reference	K8AK-VW2 100-240VAC
Catalog number	K8AKVW2100240VAC
Category	Voltage monitoring relay
Minimum order	1 Pcs
Document ID	EO-1372E78986
Generated	2026-08-02

Product Overview

Single-phase Voltage Max and Min 1-150VAC/DC 100-240VAC 2 SPDT

Monitoring relay 22.5mm wide, Single phase over or under voltage 1 to 150V AC or DC, Two SPDT, 100-240 VAC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OMRON > Monitoring Relays > K8AK

Additional Product Information

Specifications

Functions Voltage

Installation type DIN Rail

Terminal Screw

Size 22.5 mm

Supply voltage AC 100-240 V

Output type Relay

Contact description 2 x SPDT

Body color Black

ETIM for 378174 Relays (EC001438)

Feature Name

Feature Value

Type of electric connection (EF003961)

Screw connection

Voltage type (supply voltage) (EF002991)

AC

Type of voltage measuring range (EF003399)

AC/DC

Contains function DC-over voltage (EF003397)

Yes

External power supply required (EF003292)

Yes

Contains function DC-voltage hysteresis (EF003398)

Yes

With detachable clamps (EF003340)

No

Single-phase under voltage possible (EF003390)

Yes

Three-phase under voltage possible (EF003391)

No

Three-phase over voltage possible (EF003393)

No

Contains function DC-under voltage (EF003396)

Yes

Single-phase over voltage possible (EF003392)

Yes

Single-phase hysteresis possible (EF003394)

Yes

Three-phase hysteresis possible (EF003395)

No

Number of contacts as change-over contact (EF008257)

2

Number of contacts as normally open contact (EF008256)

0

Min. adjustable delay-on energization time (EF008190)

0.1 s

Max. permitted delay-on energization time (EF008189)

30 s

Min. adjustable off-delay time (EF008192)

0.1 s

Width (EF000008)

22.5 mm

Number of contacts as normally closed contact (EF008255)

0

Height (EF000040)

90 mm

Rated switch current (EF006706)

5 A

Max. permitted off-delay time (EF008191)

30 s

Depth (EF000049)

100 mm

Supply voltage AC 50 Hz (EF007532)

100 V

Response value voltage (EF008193)

1 V

Voltage m...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OMRON / K8AK-VW2 100-240VAC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.