

INDUSTRIAL COMPONENT DATA

M16-TY-24D M16 7079B M16TY24D OMRON PUSHBUTTON/INDICATOR 16mm

Brand: OMRON | Manufacturer Part Number: M16-TY-24D



Manufacturer	OMRON
MPN / Reference	M16-TY-24D
Catalog number	M16TY24D
Category	Indicator light complete
Minimum order	10 Pcs
Document ID	EO-765D2931F4
Generated	2026-07-29

Product Overview

PUSHBUTTON/INDICATOR 16mm

PUSH/INDICATOR 16mm

Indicator, round, yellow, 24VDC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OMRON > Industrial Limit switches / Pushbuttons > Special

Additional Product Information

LED, incandescent and neon lamp

Snap-in switch unit

Short mounting depth, less than 28.5mm below panel

High reliability, IP65

UL and CSA approved, conforms to EN60947-5-1

Specifications & ordering info

Ordering information

Pushbutton

Type

Display color

Order code

IP65 oil-resistant

Rectangular

Square
Round
LED
Incandescent lamp
Red
A165L-JR
A165L-AR
A165L-TR
Yellow
A165L-JY
A165L-AY
A165L-TY
Pure yellow
A165L-JPY
A165L-APY
A165L-TPY
White
A165L-JW
A165L-AW
A165L-TW
Blue
A165L-JA
A165L-AA
A165L-TA
LED
Incandescent lamp
Green
A165L-JGY
A165L-AGY
A165L-TGY
Green
A165L-JG
A165L-AG
A165L-TG
Lamp
Type
Color
Order code
Operating voltage
5 VDC
12 VDC
24 VDC
LED
Red
A16-5DSR
A16-12DSR
A16-24DSR

Yellow
A16-5DSY
A16-12DSY
A16-24DSY
Green
A16-5DSG
A16-12DSG
A16-24DSG
White
A16-5DSW
A16-12DSW
A16-24DSW
Blue
A16-5DA
A16-12DA
A16-24DA
Type
5 VAC/VDC
12 VAC/VDC
24 VAC/VDC
Incandescent lamp
A16-5
A16-12
A16-24
Case
Classification
Order code
IP65 oil-resistant
Rectangular
A165-CJM
Square
A165-CAM
Round
A165-CTM
Socket
Classification
Order code
Solder terminals
M16-0
PCB terminals
M16-0P
Screw-less clamp
M16-S
Solder terminals
Voltage-reduction
lighting
100 V

M16-T1

Screw-less clamp

100 V

M16-T1-S

200 V

M16-T2-S

Specifications

Allowable operating frequency

Mechanical

Momentary operation: 120 operations/minute max., alternate operation: 60 operations/minute max.

Electrical

20 operations/minute max.

Durability

Mechanical

Momentary operation: 2,000,000 operations min.,

alternate operation: 200,00...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OMRON / M16-TY-24D with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.