

INDUSTRIAL COMPONENT DATA

OS32C-SP1-DM-4M OS326106R OS32CSP1DM4M OMRON

Scanner laser safety 4m/15m Cable Ethernet/IP side

Brand: OMRON | Manufacturer Part Number: OS32C-SP1-DM-4M



Manufacturer	OMRON
MPN / Reference	OS32C-SP1-DM-4M
Catalog number	OS32CSP1DM4M
Category	Laser scanner
Minimum order	1 Pcs
Document ID	EO-C8DC0880F5
Generated	2026-08-03

Product Overview

Scanner laser safety 4m/15m Cable Ethernet/IP side

Safety laser scanner with measurement data, safety radius 4m, warning zone 10 m, PLd & Cat 3, EtherNet/IP, 24 VDC, side location cable exit

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	OMRON > Safety > OS32C
--------------	------------------------

Additional Product Information

Type of safety according to IEC 61496-13Maximum safety range4 mMaximum warning range15 mCommunication port(s)EtherNet/IPCable entry directionSideType of switching output of the OSSDPNPConnection methodPigtail connectorKey featuresConfigurable object resolution of 30, 40, 50 or 70 mm, Manual/auto start, Reference boundary monitoringType of protectionHand protectionDetection capability70 mmSuitable for safety functionsScan angle270 °Scanning interval0.4 HzResponse time80 msNumber of safety fields140Wavelength of the sensor905 nmNumber of protected semiconductor outputs2Number of semiconductor outputs with signalling function2Laser protection classClass 1Supply voltage DC16.8-30 VVoltage typeDCMax. output current at protected output250 mADegree of protection (IP)IP65With alert field outputAmbient temperature-10-50 °COverall length of sensor143 mmHeight of sensor105 mmWidth of sensor105 mm

ETIM for 674733 Sensors (EC002550)

Feature Name

Feature Value

Voltage type (EF000187)

DC
Type of switching output of the OSSD (EF003959)
PNP
Laser protection class (EF004027)
Class 1
Type of safety according to IEC 61496-1 (EF004105)
3
Type of interface for safety communication (EF003956)
Other
Type of electric connection (EF003961)
Cable with connector
Operation agent-safety class (EF003982)
Safety class 3
With configurable message output (EF004018)
Yes
With monitoring function downstream switching devices (EF004052)
No
Suitable for safety functions (EF001597)
Yes
With alert field output (EF0...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OMRON / OS32C-SP1-DM-4M with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.