

INDUSTRIAL COMPONENT DATA

**J7TKN-D-52 J7TK9033M J7TKND52 OMRON 40A 52A
(J7KN-50..74)**

Brand: OMRON | Manufacturer Part Number: J7TKN-D-52



Manufacturer	OMRON
MPN / Reference	J7TKN-D-52
Catalog number	J7TKND52
Category	Thermal overload relay
Minimum order	1 Pcs
Document ID	EO-F421F296EA
Generated	2026-08-05

Product Overview

40A - 52A (J7KN-50..74)

Overload relay, 3-pole, 40-52 A, direct mounting on J7KN50-74, hand and auto reset

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OMRON > Low Voltage Switchgear > J7TK Thermal overload relays

Additional Product Information

Specifications

Setting range D.O.L. (A) 40-52 A

Setting range Star-delta [A] 70-90 A

Width 68 mm

Height 102 mm

Depth 94 mm

ETIM for 118713 Low-voltage industrial controls and switchgear (EC000106)

Feature Name

Feature Value

Mounting method (EF000003)

Direct attachment

Type of electrical connection of main circuit (EF006819)

Screw connection

Release class (EF006668)

CLASS 10 A

Reset function push-button (EF011942)

Yes

Reset function input (EF011940)

No

Reset function automatic (EF011941)

Yes

Number of auxiliary contacts as change-over contact (EF003531)

0

Max. rated operation voltage Ue (EF007357)

690 V

Number of auxiliary contacts as normally closed contact (EF001377)

1

Number of auxiliary contacts as normally open contact (EF001376)

1

Adjustable current range (EF008211)

40 A

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OMRON / J7TKN-D-52 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.