

## INDUSTRIAL COMPONENT DATA

# D4BL-4DRA-A D4BL4003M D4BL4DRAA OMRON Metal 2NC+1NC 24vdc LED M20

Brand: OMRON | Manufacturer Part Number: D4BL-4DRA-A



|                 |                                    |
|-----------------|------------------------------------|
| Manufacturer    | OMRON                              |
| MPN / Reference | D4BL-4DRA-A                        |
| Catalog number  | D4BL4DRAA                          |
| Category        | Position switch with guard locking |
| Minimum order   | 1 Pcs                              |
| Document ID     | EO-01F978439B                      |
| Generated       | 2026-08-02                         |

## Product Overview

Metal 2NC+1NC 24vdc LED M20

Metallic 2NC+1NC 24Vcc LED M20

Safety door-lock switch, M20 conduit, mechanical lock, 24 VDC solenoid release, 2NC/1NO+1NC, 10 A, LED

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path OMRON &gt; Safety &gt; Others

## Additional Product Information

ETIM for 147015 Sensors (EC002593)

Feature Name

Feature Value

Degree of protection (NEMA) (EF011959)

Other

Degree of protection (IP) (EF005474)

IP67

Type of interface for safety communication (EF003956)

None

Housing material (EF001596)

Metal

Explosion safety category for gas (EF003997)

None

Explosion safety category for dust (EF003998)

None

Construction type housing (EF004008)

Cuboid

Type of switching contact (EF003591)

Slow-action switch

Type of electric connection (EF003961)

Cable entry metrical

Type of interface (EF006977)

None

With status indication (EF001602)

Yes

With escape release (EF007172)

Yes

Suitable for safety functions (EF001597)

Yes

Number of contacts as change-over contact (EF008257)

0

Rated operation current  $I_e$  at DC-13, 24 V (EF007087)

0 A

Rated operation current  $I_e$  at AC-15, 125 V (EF007082)

6 A

Height of sensor (EF007283)

46.3 mm

Number of contacts as normally open contact (EF008256)

0

Guard locking force (EF007552)

700 N

Number of safety auxiliary contacts (EF006940)

0

Rated operation current  $I_e$  at DC-13, 230 V (EF001386)

0 A

Number of contacts as normally closed contact (EF008255)

3

Width sensor (EF007094)

112 mm

Length of sensor (EF007334)

123.5 mm

Ambient temperature during operating (EF007515)

-10 °C

Rated control supply voltage magnet drive DC (EF007070)

20.4 V

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OMRON / D4BL-4DRA-A with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.