

INDUSTRIAL COMPONENT DATA

F3SJ-B1345P25 F3SB0016A F3SJB1345P25 OMRON Class IV Basic Hand 1345mm serial Connection

Brand: OMRON | Manufacturer Part Number: F3SJ-B1345P25



Manufacturer	OMRON
MPN / Reference	F3SJ-B1345P25
Catalog number	F3SJB1345P25
Category	Light curtain
Minimum order	1 Pcs
Document ID	EO-EA07E3DF32
Generated	2026-08-04

Product Overview

Class IV Basic Hand 1345mm serial Connection

Safety Light Curtain, F3SJ Basic, Type 4, 25mm resolution, range 0.2 to 7.0m, height 1345mm, PNP

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OMRON > Safety > F3SJ-A and MS Barriers

Additional Product Information

ETIM for 356744 Sensors (EC002549)

Feature Name

Feature Value

Explosion safety category for dust (EF003998)

None

Voltage type (EF000187)

DC

Type of switching output of the OSSD (EF003959)

PNP

Scope of delivery of the one-way system (EF004032)

Transmitter and receiver

Degree of protection (NEMA) (EF011959)

Other

Degree of protection (IP) (EF005474)

IP65
Type of safety according to IEC 61496-1 (EF004105)
4
Type of interface for safety communication (EF003956)
Other
Type of electric connection (EF003961)
Connector M12
Operation agent-safety class (EF003982)
Safety class 3
Explosion safety category for gas (EF003997)
None
Cascadable (EF000507)
Yes
With muting function (EF004057)
Yes
With monitoring function downstream switching devices (EF004052)
Yes
Suitable for safety functions (EF001597)
Yes
Fade-out possible (EF003955)
No
Max. output current at protected output (EF004035)
200 mA
Number of protected contact energized outputs (EF003952)
0
Number of semiconductor outputs with signalling function (EF003945)
1
Safety field height (EF004103)
1345 mm
Wavelength of the sensor (EF004132)
870 nm
Detection capability for test bodies (EF003991)
25 mm
Resolution of the light curtain (EF006784)
20 mm
Response time (EF004094)
15 ms
Number of protected semiconductor outputs (EF003951)
2
Transmission range of the safety field (EF004098)
7 m
Switching voltage of OSSD at state "high" (EF004102)
24 V
Width sensor (EF007094)
30 mm
Height of sensor (EF007283)
30 mm

Length of sensor (EF007334)
134...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OMRON / F3SJ-B1345P25 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.