

INDUSTRIAL COMPONENT DATA

D40A-1C015-F D40A6003D D40A1C015F OMRON Switch door E. Hall, 1 Aux PNP NA Cable 0.15 m + M12

Brand: OMRON | Manufacturer Part Number: D40A-1C015-F



Manufacturer	OMRON
MPN / Reference	D40A-1C015-F
Catalog number	D40A1C015F
Category	Position switch with separate actuator
Minimum order	1 Pcs
Document ID	EO-20147590A0
Generated	2026-07-31

Product Overview

Switch door E. Hall, 1 Aux PNP NA Cable 0.15 m + M12

Non-contact door switches, 1 aux output, Pigtail with M12 connector 4-pole

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OMRON > Safety > Others

Additional Product Information

Door switch typeNon-contactGuard-lockCodingBasicMaterial housingPBTAmbient temperature (operating)-10-55 °CDoor contacts NC1Door contacts NO1LED indicatorConnection methodM12 pigtail connectorCable length0.15 mCable exit directionBottomDegree of protection (IP)IP67Output typePNPShapeCuboidOverall length of sensor13 mmHeight of sensor48 mmWidth of sensor25 mmSwitch without actuator

ETIM for 355125 Sensors (EC002592)

Feature Name

Feature Value

Explosion safety category for dust (EF003998)

None

Construction type housing (EF004008)

Special construction

Type of switching contact (EF003591)

Other

Degree of protection (NEMA) (EF011959)

Other

Coating housing (EF001601)

Plastic-coated

Degree of protection (IP) (EF005474)

IP67

Type of interface for safety communication (EF003956)

None

Type of electric connection (EF003961)

Connector M12

Type of interface (EF006977)

None

Housing material (EF001596)

Plastic

Explosion safety category for gas (EF003997)

None

With status indication (EF001602)

Yes

Suitable for safety functions (EF001597)

Yes

Forced opening (EF006694)

No

Number of contacts as change-over contact (EF008257)

0

Number of contacts as normally open contact (EF008256)

1

Rated operation current I_e at AC-15, 230 V (EF001385)

0 A

Rated operation current I_e at DC-13, 125 V (EF007085)

0 A

Number of safety auxiliary contacts (EF006940)

0

Rated operation current I_e at DC-13, 24 V (EF007087)

0.013 A

Rated operation current I_e at DC-13, 230 V (EF001386)

0 A

Number of contacts as normally c...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OMRON / D40A-1C015-F with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.