

INDUSTRIAL COMPONENT DATA

E3S-CT66 E3S 7044R E3SCT66OMS OMRON Robust cc 3h Barrier 30m Vert. M12

Brand: OMRON | Manufacturer Part Number: E3S-CT66



Manufacturer	OMRON
MPN / Reference	E3S-CT66
Catalog number	E3SCT66OMS
Category	Through beam photoelectric sensor
Minimum order	1 Pcs
Document ID	EO-4E269E2EE8
Generated	2026-07-31

Product Overview

Robust cc 3h Barrier 30m Vert. M12

Photoelectric sensor, through-beam, 30m, DC, 3-wire, NPN/PNP, vertical, M12 plug-in

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OMRON > Photoelectric sensors > E3S

Additional Product Information

Oil-resistive, compact photoelectric sensor in metal housing

E3S-C

Features

Meets IP67/IP67G (oil tight) and NEMA 6P standards water/oil resistance

E3S-C meets the IP67 requirements of the IEC standards and

6P of the NEMA standards. E3S-C can be used worry-free in automotive assembly lines and other production lines where oil vapor exists. It can also be applied to food processing lines because it resists hydrogen peroxide, detergent and potassium hydroxide.

High shock resistance of 1,000 m/s²The industry's top-class photoelectric sensor features shock resistance of 1,000 m/s², which is as high as that of a proximity sensor at rated values, and vibration resistance of as high as 10 to 2,000 Hz.

Lineup of M12 metal connector joint type models Lineup of water/oil/shock-resistant M12 metal connector joint type models

are available. This series ensures ease of sensor replacement during maintenance.

NPN/PNP output selector

The operation panel has the NPN/PNP output selector. You need not prepare two NPN and PNP models for export. You need not worry about malfunctions due to noise, either.

Mutual interference prevention enhanced (Retroreflective, diffuse reflective models) Fuzzy inference is introduced into the mutual interference pre-

vention for the first time in the industry. This prevents a malfunction due to mutual interference, enabling two sensors to be mounted closely side by side.

Easy optical axis alignment

OMRON's original "automatic position compensation sys...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OMRON / E3S-CT66 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.