

INDUSTRIAL COMPONENT DATA

TL-W5MB1-M5J 0,26M TLW 7028G TLW5MB1M5J026MOMS OMRON Proximity sensor, inductive, non-shielded, 5 mm, DC, 3-..

Brand: OMRON | Manufacturer Part Number: TL-W5MB1-M5J 0,26M



Manufacturer	OMRON
MPN / Reference	TL-W5MB1-M5J 0,26M
Catalog number	TLW5MB1M5J026MOMS
Category	Inductive proximity switch
Minimum order	1 Pcs
Document ID	EO-9E0EF612E9
Generated	2026-08-03

Product Overview

Proximity sensor, inductive, non-shielded, 5 mm, DC, 3-wire, PNP-NO, 0.26 m cable with M8 3-pin connector

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OMRON > Proximity Sensors > TL-T/W

Additional Product Information

ETIM for 231966 Sensors (EC002714)

Feature Name

Feature Value

Explosion safety category for dust (EF003998)

None

Voltage type (EF000187)

DC

Construction type housing (EF004008)

Cuboid

Degree of protection (NEMA) (EF011959)

Other

Coating housing (EF001601)

Other

Mechanical mounting condition for sensor (EF004041)
Not flat

Performance level according to EN ISO 13849-1 (EF007399)
None

Type of interface for safety communication (EF003956)
None

Type of actuation (EF006949)
Metallic Target

Type of switch function (EF003963)
Normally open contact

Type of electric connection (EF003961)
Cable with connector

Type of interface (EF006977)
None

SIL according to IEC 61508 (EF009889)
None

Housing material (EF001596)
Plastic

Type of switching output (EF003962)
PNP

Explosion safety category for gas (EF003997)
None

Cascadable (EF000507)
Yes

With monitoring function downstream switching devices (EF004052)
No

Compression-resistant (EF007106)
No

Suitable for safety functions (EF001597)
No

Number of protected contact energized outputs (EF003952)
0

Number of semiconductor outputs with signalling function (EF003945)
1

Number of protected semiconductor outputs (EF003951)
0

Width sensor (EF007094)
31 mm

Height of sensor (EF007283)
18 mm

Switching distance (EF003647)
5 mm

Length of sensor (EF007334)
10 mm

Switching frequency (EF003587)
500 Hz

Number of contact energized outputs with signalling function (EF003946)

0

Supply voltage (EF004127)

12 V

Rated control supply voltage DC (EF003980)

12 V

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OMRON / TL-W5MB1-M5J 0,26M with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.