

INDUSTRIAL COMPONENT DATA

VZAB0P2BAA 3G3Z1365M OMRON V1000 single Phase 200-240VAC (1,6/1,9)Amp (0,25/0,37)KW Vector

Brand: OMRON | Manufacturer Part Number: VZAB0P2BAA



Manufacturer	OMRON
MPN / Reference	VZAB0P2BAA
Catalog number	VZAB0P2BAA
Category	Frequency converter less than 1 kV
Minimum order	1 unit
Document ID	EO-2E46E3E9C0
Generated	2026-08-03

Product Overview

V1000 single Phase 200-240VAC (1,6/1,9)Amp (0,25/0,37)KW Vector

V1000 Single Phase 200VAC (1.6/1.9)Amp (0.25/0.37)KW Vector

V1000 inverter, 1~ 200 VAC, 0.25 kW, 1.6 A, sensorless vector, max. output freq. 400Hz

STRUCTURED PRODUCT DATA

Technical Specifications

TECHNICAL ATTRIBUTE	VALUE
Mains frequency (EF006783)	50/60 Hz
Type of converter (EF006978)	Other
Degree of protection (NEMA) (EF011959)	Other
Degree of protection (IP) (EF005474)	IP20
Number of phases input (EF007117)	1
Number of phases output (EF006998)	3
With PC connection (EF006107)	Yes
Supporting protocol for PROFI-safe (EF007526)	No
Supporting protocol for PROFIBUS (EF003052)	Yes
Supporting protocol for DeviceNet Safety (EF007520)	No
Supporting protocol for TCP/IP (EF003050)	No
Supporting protocol for other bus systems (EF003062)	Yes
Supporting protocol for Foundation Fieldbus (EF007522)	No
Application in domestic- and commercial area permitted (EF007295)	No

CONTINUED

Technical Specifications

TECHNICAL ATTRIBUTE	VALUE
4-quadrant operation possible (EF006803)	Yes
Supporting protocol for SafetyBUS p (EF007527)	No
Supporting protocol for SERCOS (EF006657)	No
With control element (EF001538)	Yes
Supporting protocol for Modbus (EF003057)	Yes
Supporting protocol for KNX (EF003055)	No
Application in industrial area permitted (EF007294)	Yes
Supporting protocol for PROFINET CBA (EF007524)	No
Supporting protocol for LON (EF003017)	No
Supporting protocol for SUCONET (EF003060)	No
With optical interface (EF003028)	No
Supporting protocol for EtherNet/IP (EF007521)	No
Supporting protocol for CAN (EF003053)	Yes
Supporting protocol for AS-Interface Safety at Work (EF007519)	No
Supporting protocol for INTERBUS (EF003054)	No
Supporting protocol for Data-Highway (EF003058)	No
Supporting protocol for PROFINET IO (EF007525)	Yes
Supporting protocol for ASI (EF003051)	No
Supporting protocol for DeviceNet (EF003059)	Yes
Supporting protocol for INTERBUS-Safety (EF006662)	No
Integrated breaking resistance (EF007293)	Yes
Max. output frequency (EF007350)	400 Hz
Number of HW-interfaces other (EF003027)	0
Number of HW-interfaces parallel (EF003026)	0
Number of interfaces PROFINET (EF006932)	0
Number of HW-interfaces industrial Ethernet (EF003020)	0
Max. output at linear load at rated output voltage (EF007364)	0.25 kW
Relative symmetric net voltage tolerance (EF007453)	10 %
Number of HW-interfaces USB (EF003025)	0
Width (EF000008)	68 mm
Number of HW-interfaces RS-232 (EF003021)	0
Number of HW-interfaces RS-422 (EF003022)	1
Max. output at quadratic load at rated output voltage (EF007366)	0.37 kW

CONTINUED

Technical Specifications

TECHNICAL ATTRIBUTE	VALUE
Number of HW-interfaces RS-485 (EF003023)	1
Nominal output current I2N (EF009561)	1.6 A
Number of HW-interfaces serial TTY (EF003024)	0
Height (EF000040)	128 mm
Max. output voltage (EF009560)	240 V
Depth (EF000049)	76 mm
Relative symmetric net frequency tolerance (EF007454)	5 %
Mains voltage (EF006780)	200 V

Classification & Catalog Path

Catalog path	OMRON > Frequency inverters > V1000
--------------	-------------------------------------

Additional Product Information

Specifications

Inverter control method Open loop V/f, Open loop vector

Drive supply voltage 230 V single phase

Max. motor output at constant torque (HD) 0.25 kW

Max. motor output at variable torque (ND) 0.37 kW

Built in EMC filter

Degree of protection (IP) IP20

Finless type

Compatible motor type Induction or asynchronous motor, Permanent magnet motor

Regenerative solutions As inverter option

Communication port(s) MODBUS Slave, Serial RS-422, Serial RS-485

Communication option(s) CANopen, DeviceNet Slave, EtherCAT Slave, EtherNet/IP, MECHATROLINK II Slave,

MODBUS/TCP, POWERLINK, PROFIBUS DP Slave, PROFINET Slave

Height 128 mm

Width 68 mm

Depth 76 mm

Weight 700 g

Accessories

SI-EN3/V EtherNet/IP option board for V1000 inverter

SI-EP3/V V1000 option card - PROFINET

SI-ES3/V Ethercat option board for V1000

SI-N3/V DeviceNet option board for V1000 inverter

SI-P3/V PROFIBUS DP option board for V1000 inverter

ETIM for 234259 Low-voltage industrial controls and switchgear (EC001857)

Feature Name

Feature Value

Mains frequency (EF006783)

50/60 Hz

Type of converter (EF006978)

Other

Degree of p...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OMRON / VZAB0P2BAA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.