

INDUSTRIAL COMPONENT DATA

WL-5H5104 WL 9165R WL5H5104 OMRON Actuator,the End of the career of general purpose, IP67, break fast, 2-cir..

Brand: OMRON | Manufacturer Part Number: WL-5H5104



Manufacturer	OMRON
MPN / Reference	WL-5H5104
Catalog number	WL5H5104
Category	Drive head for position switches/hinge switches
Minimum order	1 Pcs
Document ID	EO-B2A3022823
Generated	2026-08-01

Product Overview

Actuator,the End of the career of general purpose, IP67, break fast, 2-circuit, rupture, double, SPST-NO / SPST

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **OMRON > Industrial Limit switches / Pushbuttons > WL**

Additional Product Information

Improved durability and performance
Reduced part numbers
Easy wiring
Direct and pre-wiring
Ground terminal models are approved by EN and IEC and bear the CE marking
UL,CSA
Specifications & ordering info
Ordering Information
Actuator type
Contact Form and features
Connection method
CE Mark
Order code
Roller lever R38
DPDB1

Screw terminal (Pg13,5 conduit with ground terminal)2

Yes

WLCA2-2NG-N

Adjustable roller lever: R25 to 89 mm, pretravel $15^{\circ} \pm 5^{\circ}$

DPDB, Heat-resistant: 5 to 120°C

WLCA12-THG-N

Adjustable roller lever: R25 to 89 mm, pretravel $15^{\circ} \pm 5^{\circ}$

DPDB, LED

WLCA12-GLD-N

Roller lever R50, pretravel $15^{\circ} \pm 5^{\circ}$

DPDB

WLCA2-7G-N

Roller lever R63, pre-travel $15^{\circ} \pm 5^{\circ}$

DPDB

WLCA2-8G-N

Adjustable rod lever: 25 to 140 mm, pretravel $15^{\circ} \pm 5^{\circ}$

DPDB, Heat-resistant: 5 to 120°C

WLCL-THG-N

Adjustable rod lever: 25 to 140 mm, pretravel $15^{\circ} \pm 5^{\circ}$

DPDB, LED,

Pre-wired Connector M12 (Smart Click), with ground terminal

WLCL-2NLD-DGJ-N

Roller lever R38, High sensitive pre-travel $10^{\circ} + 2/-1^{\circ}$

DPDB, LED

WLG2-LDFS-DGJS-N

Specifications

Characteristics

Degree of protection

IP67

Durability3

Mechanical

15,000,000 operations min.4

Electrical

750,000 operations min.5

Operating speed

1 mm/s to 1 m/s (in case of WLCA2-N)

Operating frequency

Mechanical

120 operations/minute min.

Electrical

30 operations/minute min.

Rated frequency

50/60 Hz

Insulation resistance

100 M Ω min. (at 500 VDC)

Contact resistance

25 m Ω max. (initial value for the built-in switch when tested alone)

Dielectric strength
Between terminals of the same p...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OMRON / WL-5H5104 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.