

INDUSTRIAL COMPONENT DATA

WL-7H200 WL 9170E WL7H200 OMRON Actuator Plunger

Brand: OMRON | Manufacturer Part Number: WL-7H200



Manufacturer	OMRON
MPN / Reference	WL-7H200
Catalog number	WL7H200
Category	Drive head for position switches/hinge switches
Minimum order	1 Pcs
Document ID	EO-E7B7CA76BC
Generated	2026-08-02

Product Overview

Actuator Plunger

Plunger Actuator

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OMRON > Industrial Limit switches / Pushbuttons > WL

Additional Product Information

Improved durability and performance

Reduced part numbers

Easy wiring

Direct and pre-wiring

Ground terminal models are approved by EN and IEC and bear the CE marking

UL,CSA

Specifications & ordering info

Ordering Information

Actuator type

Contact Form and features

Connection method

CE Mark

Order code

Roller lever R38

DPDB1

Screw terminal (Pg13,5 conduit with ground terminal)2

Yes

WLCA2-2NG-N

Adjustable roller lever: R25 to 89 mm, pretravel $15^{\circ} \pm 5^{\circ}$

DPDB, Heat-resistant: 5 to 120°C

WLCA12-THG-N

Adjustable roller lever: R25 to 89 mm, pretravel $15^{\circ} \pm 5^{\circ}$

DPDB, LED

WLCA12-GLD-N

Roller lever R50, pretravel $15^{\circ} \pm 5^{\circ}$

DPDB

WLCA2-7G-N

Roller lever R63, pre-travel $15^{\circ} \pm 5^{\circ}$

DPDB

WLCA2-8G-N

Adjustable rod lever: 25 to 140 mm, pretravel $15^{\circ} \pm 5^{\circ}$

DPDB, Heat-resistant: 5 to 120°C

WLCL-THG-N

Adjustable rod lever: 25 to 140 mm, pretravel $15^{\circ} \pm 5^{\circ}$

DPDB, LED,

Pre-wired Connector M12 (Smart Click), with ground terminal

WLCL-2NLD-DGJ-N

Roller lever R38, High sensitive pre-travel $10^{\circ} + 2/-1^{\circ}$

DPDB, LED

WLG2-LDFS-DGJS-N

Specifications

Characteristics

Degree of protection

IP67

Durability3

Mechanical

15,000,000 operations min.4

Electrical

750,000 operations min.5

Operating speed

1 mm/s to 1 m/s (in case of WLCA2-N)

Operating frequency

Mechanical

120 operations/minute min.

Electrical

30 operations/minute min.

Rated frequency

50/60 Hz

Insulation resistance

100 M Ω min. (at 500 VDC)

Contact resistance

25 m Ω max. (initial value for the built-in switch when tested alone)

Dielectric strength
Between terminals of the same p...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OMRON / WL-7H200 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.