

INDUSTRIAL COMPONENT DATA

XS2F-M12PVC3S20M XS2F0767H XS2FM12PVC3S20M OMRON M12 PVC with a Straight-through cable 3-wire 20m

Brand: OMRON | Manufacturer Part Number: XS2F-M12PVC3S20M



Manufacturer	OMRON
MPN / Reference	XS2F-M12PVC3S20M
Catalog number	XS2FM12PVC3S20M
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-BE9583906D
Generated	2026-08-06

Product Overview

M12 PVC with a Straight-through cable 3-wire 20m

M12 PVC with Straight Cable 3 Wires 20m

Sensor cable, M12 straight socket (female), 3-poles, A coded, PVC fire-retardant cable, IP67, 20 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OMRON > Proximity Sensors > Accessories

Additional Product Information

UsageCable with connectorConnector 1M12 straight socketConnector 2Open endsNumber of pin contact3Cable specificationsPVCCable length20 mFeaturesFire retardantColorBlackColor coverBlackMaterial nutBrassLED indicator ETIM for 419212 Sensors (EC001855)

Feature Name

Feature Value

Type of electrical connection, field-sided (EF005525)

M12

Cable type (EF000081)

Multi-core

Colour cable sheath (EF008249)

Black

Degree of protection (IP) (EF005474)

IP67

Type of plug-in contact, field sided (EF006269)
Female (bus)
Positioning cable feed, field-sided (EF005928)
Straight
Material of contact surface (EF004020)
Nickel/gold
Material contact body (EF008248)
CuZn
Positioning cable feed, box-sided (EF005927)
Straight
Material of cable sheath (EF004136)
Polyvinyl chloride (PVC)
Type of electrical connection, box-sided (EF005524)
Free conductor end
Screened (EF000881)
No
Halogen free (EF000025)
No
With LED indication (EF005950)
No
Continuity resistance (EF003992)
40 mOhm
Rated voltage (EF000228)
125 V
Cable length (EF000536)
20 m
Rated current In (EF008250)
4 A
Number of poles (EF001391)
3
Permitted cable outer temperature after assembling without vibration (EF001686)
-10 °C
Permitted cable outer temperature during assembling/handling (EF001685)
-10 °C

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OMRON / XS2F-M12PVC3S20M with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.