

**INDUSTRIAL COMPONENT DATA**

# XS3F-M422-405-A XS3F0036G XS3FM422405A OMRON With cable, Angled, 4 wire, 5m M8

Brand: OMRON | Manufacturer Part Number: XS3F-M422-405-A



|                 |                            |
|-----------------|----------------------------|
| Manufacturer    | OMRON                      |
| MPN / Reference | XS3F-M422-405-A            |
| Catalog number  | XS3FM422405A               |
| Category        | Sensor-actuator patch cord |
| Minimum order   | 5 Pcs                      |
| Document ID     | EO-8E1BC412BA              |
| Generated       | 2026-08-04                 |

## Product Overview

With cable, Angled, 4 wire, 5m M8

Sensor cable, M8 right-angle socket (female), 4-poles, PVC standard cable, IP67, 5 m

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path      OMRON &gt; Proximity Sensors &gt; Accessories

## Additional Product Information

UsageCable with connectorConnector 1M8 right-angle socketConnector 2Open endsNumber of pin contact4Cable

specificationsPVCCable length5 mColorBlackColor coverBlackMaterial nutBrassLED indicator

ETIM for 141967 Sensors (EC001855)

Feature Name

Feature Value

Type of electrical connection, field-sided (EF005525)

M8

Cable type (EF000081)

Multi-core

Colour cable sheath (EF008249)

Black

Degree of protection (IP) (EF005474)

IP67

Type of plug-in contact, field sided (EF006269)

Female (bus)  
Positioning cable feed, field-sided (EF005928)  
Angled  
Material of contact surface (EF004020)  
Nickel/gold  
Material contact body (EF008248)  
Other  
Positioning cable feed, box-sided (EF005927)  
Other  
Material of cable sheath (EF004136)  
Polyvinyl chloride (PVC)  
Type of electrical connection, box-sided (EF005524)  
Free conductor end  
Screened (EF000881)  
No  
Halogen free (EF000025)  
No  
Vulcanize (EF004115)  
No  
With LED indication (EF005950)  
No  
Continuity resistance (EF003992)  
40 mOhm  
Rated voltage (EF000228)  
125 V  
Cable length (EF000536)  
5 m  
Rated current I<sub>n</sub> (EF008250)  
1 A  
Number of poles (EF001391)  
4  
Permitted cable outer temperature after assembling without vibration (EF001686)  
-25 °C  
Permitted cable outer temperature during assembling/handling (EF001685)  
-25 °C

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OMRON / XS3F-M422-405-A with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.