

INDUSTRIAL COMPONENT DATA

XS3W-M321-310-R XS3W0182G XS3WM321310R OMRON

Cable with connectors on both cable ends, M8 straight socket (f..

Brand: OMRON | Manufacturer Part Number: XS3W-M321-310-R



Manufacturer	OMRON
MPN / Reference	XS3W-M321-310-R
Catalog number	XS3WM321310R
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-CCB33E2B9A
Generated	2026-08-06

Product Overview

Cable with connectors on both cable ends, M8 straight socket (female), M8 straight plug (male), 3-poles, PVC robot cable, IP67, 10 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	OMRON > Proximity Sensors > Accessories
--------------	---

Additional Product Information

UsageExtension cableConnector 1M8 straight socketConnector 2M8 straight plugNumber of pin contact3Cable specificationsPVCCable length10 mFeaturesRoboticColorBlackColor coverBlackMaterial nutBrassLED indicator ETIM for 701412 Sensors (EC001855)

Feature Name

Feature Value

Type of electrical connection, field-sided (EF005525)

M8

Cable type (EF000081)

Multi-core

Colour cable sheath (EF008249)

Black

Degree of protection (IP) (EF005474)

IP67

Type of plug-in contact, field sided (EF006269)

Female (bus)

Positioning cable feed, field-sided (EF005928)

Straight

Material of contact surface (EF004020)

Nickel/gold

Material contact body (EF008248)

Other

Type of plug-in contact, box-sided (EF008386)

Male (plug)

Positioning cable feed, box-sided (EF005927)

Straight

Material of cable sheath (EF004136)

Polyvinyl chloride (PVC)

Type of electrical connection, box-sided (EF005524)

M8

Screened (EF000881)

No

Halogen free (EF000025)

No

Vulcanize (EF004115)

No

With LED indication (EF005950)

No

Continuity resistance (EF003992)

40 mOhm

Rated voltage (EF000228)

125 V

Cable length (EF000536)

10 m

Rated current In (EF008250)

1 A

Number of poles (EF001391)

3

Permitted cable outer temperature after assembling without vibration (EF001686)

-25 °C

Permitted cable outer temperature during assembling/handling (EF001685)

-25 °C

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OMRON / XS3W-M321-310-R with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.