

INDUSTRIAL COMPONENT DATA

XS3W-M8PUR3SS2M XS3W0128B XS3WM8PUR3SS2M,1

OMRON Cable with connectors at both ends of cable, M8 straight co..

Brand: OMRON | Manufacturer Part Number: XS3W-M8PUR3SS2M



Manufacturer	OMRON
MPN / Reference	XS3W-M8PUR3SS2M
Catalog number	XS3WM8PUR3SS2M,1
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-0898520165
Generated	2026-08-06

Product Overview

Cable with connectors at both ends of cable, M8 straight connector (female), M8 straight connector (male), 3 poles, PUR robot cable, IP67, 2 m

Sensor cable, M8 straight socket (female), M8 straight plug (male), 3-poles, PUR fire-retardant halogen free cable, IP67, 2 m

Cable with connectors on both cable ends, M8 straight socket (female), M8 straight plug (male), 3-poles, PUR cable, IP67, 2 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	OMRON > Proximity Sensors > Accessories
--------------	---

Additional Product Information

UsageExtension cableConnector 1M8 straight socketConnector 2M8 straight plugNumber of pin contact3Cable specificationsPURCable length2 mFeaturesFire retardantColorBlackColor coverBlackMaterial nutBrassLED indicator ETIM for 723570 Sensors (EC001855)

Feature Name

Feature Value

Type of electrical connection, field-sided (EF005525)

M8

Cable type (EF000081)

Multi-core
Colour cable sheath (EF008249)
Black
Degree of protection (IP) (EF005474)
IP67
Type of plug-in contact, field sided (EF006269)
Female (bus)
Positioning cable feed, field-sided (EF005928)
Straight
Type of plug-in contact, box-sided (EF008386)
Male (plug)
Positioning cable feed, box-sided (EF005927)
Straight
Material of cable sheath (EF004136)
Polyurethane (PUR)
Type of electrical connection, box-sided (EF005524)
M8
Screened (EF000881)
No
Halogen free (EF000025)
Yes
Vulcanize (EF004115)
No
With LED indication (EF005950)
No
Continuity resistance (EF003992)
40 mOhm
Rated voltage (EF000228)
125 V
Cable length (EF000536)
2 m
Rated current I_n (EF008250)
1 A
Number of poles (EF001391)
3
Permitted cable outer temperature after assembling without vibration (EF001686)
-10 °C
Permitted cable outer temperature during assembling/handling (EF001685)
-10 °C

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OMRON / XS3W-M8PUR3SS2M with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.