

INDUSTRIAL COMPONENT DATA

XW2Z-0250FN-L XW2Z0525F XW2Z0250FNL OMRON Cable connection I/O, MIL40 to toe, L 250 cm

Brand: OMRON | Manufacturer Part Number: XW2Z-0250FN-L



Manufacturer	OMRON
MPN / Reference	XW2Z-0250FN-L
Catalog number	XW2Z0250FNL
Category	PLC connection cable
Minimum order	1 Pcs
Document ID	EO-8167A654A2
Generated	2026-08-06

Product Overview

Cable connection I/O, MIL40 to toe, L = 250 cm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OMRON > Control Systems > XW2

Additional Product Information

FeaturesLimit switch with basic plastic housing

The Z series of basic switches in plastic housing provide the same electrical and mechanical switching capability and lifetime as standard limit switches. But with the basic plastic housing the basic switches are an ideal solution with best value for money for uncritical environments or when separately encased in subassemblies.

Cost efficient basic plastic housing for subassemblies

Same electrical and mechanical switching ratings as standard limit switches

Ordering information

Actuator type1

Order code2

Solder terminal

Screw terminal

Pin plunger

Z-15G

Z-15G-B

Short spring plunger

Z-15GD
Z-15GD-B
Leaf spring
Z-15GL
Z-15GL-B
Reverse hinge lever
Z-15GM
Z-15GM-B
Reverse hinge roller lever
Z-15GM2
Z-15GM2-B
Plunger with M12 mounting
Z-15GQ
Z-15GQ-B
Hinge lever
Z-15GW
Z-15GW-B
Hinge roller lever
Z-15GW2
Z-15GW2-B
Specifications
Rated voltage
Non-inductive load
Inductive load
Resistive load
Lamp load
Inductive load
Motor load
NC
NO
NC
NO
NC
NO
NC
NO
125 VAC
15 A
3 A
1.5 A
15 A
5 A
2.5 A
250 VAC
15 A
2.5 A
1.25 A

15 A
3 A
1.5 A
8 VDC
15 A
3 A
1.5 A
15 A
5 A
2.5 A
14 VDC
15 A
3 A
1.5 A
10 A
5 A
2.5 A
30 VDC
6 A
3 A
1.5 A
5 A
5 A
2.5 A
125 VDC
0.5 A3
0.5 A
0.5 A
0.05 A
0.05 A
0.05 A
Durability
Mechanical
10,000,000 operations min.
Electrical
500,000 operations min.
Operating speed
Plunger
0.01 mm to 1 m/s
Operating frequency
Mechanical
240 operations/min
Electrical
20 operations/min
Ambient temperature
Operating
-25 to 80°C (with no icin...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OMRON / XW2Z-0250FN-L with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.