

INDUSTRIAL COMPONENT DATA

ZX-LD40L ZX 0006B ZXLD40L OMRON Reflex laser 40±10 mm 2 μm Beam linear

Brand: OMRON | Manufacturer Part Number: ZX-LD40L



Manufacturer	OMRON
MPN / Reference	ZX-LD40L
Catalog number	ZXLD40L
Category	Optical distance sensor
Minimum order	1 Pcs
Document ID	EO-9B3EF8A3E1
Generated	2026-08-05

Product Overview

Reflex laser 40±10 mm 2 μm Beam linear

Laser displacement sensor head, 40+/-10mm, line beam (requires amplifier), 0.5 m cable

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OMRON > Advanced sensors > ZX

Additional Product Information

Reference distance40 mmRelative linearity deflection0.2 %Measuring range length30-50 mmRepeat accuracy2 μmSpot size2 mm x 75 μmSensing methodDiffuse reflectiveMaterial housingPBTDegree of protection (IP)IP50

ETIM for 106269 Sensors (EC001825)

Feature Name

Feature Value

Explosion safety category for dust (EF003998)

None

Voltage type (EF000187)

DC

Construction type housing (EF004008)

Cuboid

Laser protection class (EF004027)

Class 2

Degree of protection (NEMA) (EF011959)

Other
Degree of protection (IP) (EF005474)
IP50
Standard for interfaces (EF004017)
Analogue
Setting procedure (EF003994)
Teach-In
Scanning principle (EF003935)
Reflection system
Type of analogy output (EF003958)
Other
Material of optical surface (EF004134)
Glass
Sensing mode (EF007503)
Light-/dark switching
Type of switch function (EF003963)
Other
Type of electric connection (EF003961)
Cable with connector
Housing material (EF001596)
Plastic
Type of light (EF004029)
Laser diode, red light
Material of cable sheath (EF004136)
Polyvinyl chloride (PVC)
Type of switching output (EF003962)
Other
Operation agent-safety class (EF003982)
Safety class 3
Explosion safety category for gas (EF003997)
None
Measuring principle for optical distance measurement (EF004060)
Triangulation
With time function (EF003582)
No
Pre failure notice (EF004129)
No
AWG-number (EF007010)
28
Relative linearity deflection (EF004034)
0.2 %
Signalling interval (EF003964)
6600 Hz
Light dot (EF004030)
0.15 mm²
Width sensor (EF007094)
17 mm

Height of...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OMRON / ZX-LD40L with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.