

INDUSTRIAL COMPONENT DATA

AFP7RTD8 PANASONIC FP7 temperature sensors unit 8 channels (triplex), PT100(-215°C bis +665°C), jPT100, Pt100..

Brand: PANASONIC | Manufacturer Part Number: AFP7RTD8



Manufacturer	PANASONIC
MPN / Reference	AFP7RTD8
Catalog number	AFP7RTD8
Category	FP7 Programmable controllers
Minimum order	1 unit
Document ID	EO-B8937C8B29
Generated	2026-07-31

Product Overview

AFP7RTD8 PANASONIC FP7 temperature sensors unit 8 channels (triplex), PT100(-215°C bis +665°C), jPT100, Pt100..

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PANASONIC > FP7 Programmable controllers
--------------	--

Additional Product Information

Product Number AFP7RTD8

Part Number AFP7RTD8

Product FP7 Temperature input units

Product name FP7 Temperature input units

Item Specifications

Product Number AFP7RTD8

Part Number AFP7RTD8

Number of channels 8 channels

Input range(resolution): Resistance temperature detector (resolution: 0.1 °C) Pt100 (1): -100.0 to 200.0degrees

Pt100 (2): -200.0 to 650.0degrees

JPt100 (1): -100.0 to 200.0degrees

JPt100 (2): -200.0 to 650.0degrees

Pt1000: -100.0 to 100.0degrees

Conversion speed 25 ms/channel + 25 ms

Add the drift compensation measuring time to the number of measuring channels.

Overall accuracy plus or minus 0.1%F.S.or less(at +25degrees +77degrees Fahrenheit)
plus or minus 0.3%F.S.or less(at 0 to +55degrees +32 to +131degrees Fahrenheit)
Allowable signal source resistance R.T.D. input: 30 Ohm (three wires balanced)
Insulation method:Between input terminals and internal circuit Photocoupler and isolated DC/DC converter
Insulation method:Between channels PhotoMOS relay
Conversion execution / non-execution channel setting Selectable per channel unit
Input range change method Selectable per channel
Digital processing:Averaging Cycle, time, moving
Digital processing:Offset setting Any value within plus or minus 3,000
Digital processing:Gain setting plus or minus 10%
Comparison of upper and lower limit values Selectable for one channel
Max. and min. value holding Selectable for one channel
Broken wire detection Available
Connection method Connector type terminal block

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PANASONIC / AFP7RTD8 with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.