

INDUSTRIAL COMPONENT DATA

UCX491P CX491P CX-491-P PANASONIC retroreflective type, 3m, PNP, cable 2m

Brand: PANASONIC | Manufacturer Part Number: UCX491P



Manufacturer	PANASONIC
MPN / Reference	UCX491P
Catalog number	UCX491P
Category	Miniature Photoelectric Sensors - PANASONIC
Minimum order	1 unit
Document ID	EO-BA54A4EC54
Generated	2026-07-31

Product Overview

UCX491P CX491P CX-491-P PANASONIC retroreflective type, 3m, PNP, cable 2m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PANASONIC > Miniature Photoelectric Sensors - PANASONIC > CX400 Compact Sensor

Additional Product Information

Product Number CX-491-P

Part Number CX-491-P

Product Compact Photoelectric Sensor

Details Retroreflective(With polarizing filters)

Product name Compact Photoelectric Sensor CX-400 Ver.2

Item Specifications

Product Number CX-491-P

Part Number CX-491-P

CE marking directive compliance EMC Directive, RoHS Directive

Sensing range 3 m9.843 ft

(Note) The sensing range and the sensing object of the retroreflective type sensor are specified for the RF-230 reflector. The sensing range represents the actual sensing range of the sensor.

Sensing object Ø50 mmØ1.969 in or more opaque, translucent or specular object

(Note) The sensing range and the sensing object of the retroreflective type sensor are specified for the RF-230 reflector. The sensing range represents the actual sensing range of the sensor.

(Note) Make sure to confirm detection with an actual sensor before use.

Hysteresis -

Repeatability(perpendicular to sensing axis) 0.5 mm0.020 in or less

Supply voltage 12 to 24 V DC plus or minus 10 % Ripple P-P 10 % or less

Current consumption 13 mA or less

Output PNP open-collector transistor

- Maximum source current: 100 mA

- Applied voltage: 30 V DC or less (between output and +V)

- Residual voltage: 2 V or less (at 100 mA source current), 1 V or less (at 16 mA source current)

Output:Output operation Switchable either Light-ON or Dark-ON

Output:Short-circuit protection Incorporated

Response time 1 ms or less

Operation indicator Orange LED(lights up when the output is ON)

(incorporated....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PANASONIC / UCX491P with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.