

INDUSTRIAL COMPONENT DATA

UEXF1 EXF1 EX-F1 PANASONIC Pipe mountable liquid level sensor, NPN, 12-24 V DC

Brand: PANASONIC | Manufacturer Part Number: UEXF1

Panasonic
INDUSTRY

Manufacturer	PANASONIC
MPN / Reference	UEXF1
Catalog number	UEXF1
Category	Special Photoelectric Sensors - PANASONIC
Minimum order	1 unit
Document ID	EO-1DDF745601
Generated	2026-08-01

Product Overview

UEXF1 EXF1 EX-F1 PANASONIC Pipe mountable liquid level sensor, NPN, 12-24 V DC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PANASONIC > Special Photoelectric Sensors - PANASONIC

Additional Product Information

Product Number EX-F1

Part Number EX-F1

Product Pipe-mountable Liquid Level Detection Sensor

Details Amplifier built-in, Pipe-mountable

Product name Pipe-mountable Liquid Level Detection Sensor EX-F1

Item Specifications

Product Number EX-F1

Part Number EX-F1

CE marking directive compliance EMC Directive, RoHS Directive

Sensing object Liquid

(Note):Unclear or highly viscous liquid may not be detected stably.

Applicable pipe diameter Outer dia. $\varnothing 6$ to $\varnothing 13$ mm $\varnothing 0.236$ to $\varnothing 0.512$ in transparent resin pipe

[PFA (Fluorine resin) or equivalently transparent pipe, wall thickness 1 mm 0.039 in]

(Note:Do not use the sensor with pipes other than the above specified.)

Supply voltage 12 to 24 V DC ± 10 % Ripple P-P 10 % or less

Current consumption 30 mA or less

(Note:Unclear or highly viscous liquid may not be detected stably.)

Output NPN open-collector transistor

- Maximum sink current: 100 mA

- Applied voltage: 30 V DC or less (between output and 0 V)

- Residual voltage: 1 V or less (at 100 mA sink current), 0.4 V or less (at 16 mA sink current)

Output:Output operation Switchable either Light-ON (Liquid-absent-ON) or Dark-ON (Liquid-present-ON)

Output:Short-circuit protection Incorporated

Response time 2 ms or less

Operation indicator Red LED (lights up when the output is ON)

Ambient temperature -10 to +55 °C+14 to +131 °F(No dew condensation or icing allowed), Storage: -20 to +70 °C-4 to +158 °F

(Note:Liquid being detected should also be kept within the rated ambient temperature range.)

Ambie...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PANASONIC / UEXF1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.