


INDUSTRIAL COMPONENT DATA

UEXZ11FBP EX-Z11FB-P PANASONIC Thru beam, 50mm, front sensing, Dark-ON, PNP, cable 2m

Brand: PANASONIC | Manufacturer Part Number: UEXZ11FBP



Manufacturer	PANASONIC
MPN / Reference	UEXZ11FBP
Catalog number	UEXZ11FBP
Category	Miniature Photoelectric Sensors - PANASONIC
Minimum order	1 unit
Document ID	EO-EB833ACA5D
Generated	2026-08-03

Product Overview

UEXZ11FBP EX-Z11FB-P PANASONIC Thru beam, 50mm, front sensing, Dark-ON, PNP, cable 2m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PANASONIC > Miniature Photoelectric Sensors - PANASONIC > EX10 Ultra-slim type photoelectric sensor**

Additional Product Information

Product Number EX-Z11FB-P

Part Number EX-Z11FB-P

Product Ultra-minute Photoelectric Sensor

Details Thru-beam [Front sensing]

Product name Ultra-minute Photoelectric Sensor EX-Z

Item Specifications

Product Number EX-Z11FB-P

Part Number EX-Z11FB-P

Applicable regulations and certifications CE Marking (EMC Directive, RoHS Directive), UKCA Marking (EMC Regulations, RoHS Regulations), UL/c-UL Certification

Output operation Dark-ON

Sensing range 50 mm 1.969 in

Min. sensing object $\varnothing 0.3$ mm $\varnothing 0.012$ in opaque object (Completely beam interrupted object)(Setting distance between emitter and receiver: 50 mm 1.969 in)

Repeatability(perpendicular to sensing axis) 0.02 mm 0.001 in or less

Supply voltage 12 to 24 V DC $\pm 10\%$ Ripple P-P 10 % or less

Current consumption Emitter: 10 mA or less

Receiver: 10 mA or less

Output PNP open-collector transistor

- Maximum source current: 20 mA

- Applied voltage: 30 V DC or less (between output and +V)

- Residual voltage: 1.5 V or less (at 20 mA source current)

Output: Short-circuit protection Incorporated

Response time 0.5 ms or less

Operation indicator Orange LED (Lights up when the sensing output is ON)

Stability indicator Green LED (Lights up under the stable light received condition or the stable dark condition)

Protection IP67 (IEC)

Ambient temperature -10 to +55 °C 14 to +131 °F (No dew condensation or icing allowed), Storage: -30 to +70 °C -22 to +158 °F

Ambient humidity 35 to 85 % RH, Storage: 35 to 85 % RH

Ambient illuminance Incandescent light: 5,000....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PANASONIC / UEXZ11FBP with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.