

INDUSTRIAL COMPONENT DATA

UFT40V FT-40V PANASONIC Vacuum resistant optical fiber, barrier, M4, temperature range -30 to 300°C, detecti..

Brand: PANASONIC | Manufacturer Part Number: UFT40V

Panasonic
INDUSTRY

Manufacturer	PANASONIC
MPN / Reference	UFT40V
Catalog number	UFT40V
Category	Fiber - PANASONIC
Minimum order	1 unit
Document ID	EO-738A8AECDF
Generated	2026-08-01

Product Overview

UFT40V FT-40V PANASONIC Vacuum resistant optical fiber, barrier, M4, temperature range -30 to 300°C, detecti..

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PANASONIC > Fiber - PANASONIC > VACUUM-RESISTANT type optical fibers

Additional Product Information

Product Number FT-40V
Part Number FT-40V
Product Thru-beam type Fiber
Details Vacuum-resistant Fiber
Product name One-Touch Connection System Vacuum-resistant Fibers
Item Specifications
Product Number FT-40V
Part Number FT-40V
Sensing mode Thru-beam type
Fiber type Vacuum-resistant
Fiber type(?????) Particular use
Fiber head dia. M4
Fiber head dia.(?????) 02##M4
Fiber head length 30 mm
With sleeve No

Beam direction Top-view
Beam axis dia./ Spot diameter dia. 1.3 mm
Fiber cable length 1m
Allowable bending radius R25mm
Allowable bending radius(????) 08##R25mm
Free-cut Not available
Semi-custom Fiber length change
Mounting lens Available
Applicable lens FV-LE1, FV-SV1, FV-SV2
Mounting protective tube Not available
Application Vacuum-resistant
Environmental resistance : Ambient temperature MAX 300 degrees
Environmental resistance : Ambient temperature MAX(????) 06##201-300 degrees
Environmental resistance : Ambient temperature MIN -30 degrees
Environmental resistance : Ambient temperature MIN(????) 04##-30 degrees
Sensing range(??) 07##701-1000mm
Sensing range(STD) 270 mm 10.630 in (FX-500 series)
Sensing range(HYPR) 1,000 mm 39.370 in (FX-500 series)
Sensing range(U-LG) 590 mm 23.228 in (FX-500 series)
Sensing range(LONG) 470 mm 18.504 in (FX-500 series)
Sensing range(FAST) 160 mm 6.299 in (FX-500 series)
Sensing range(H-SP) 55 mm 2.165 in (FX-500 series)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PANASONIC / UFT40V with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.