

INDUSTRIAL COMPONENT DATA

UFT43 FT-43 PANASONIC Fiber (thru-beam, bending radius R4, M4, 2m, IP67)

Brand: PANASONIC | Manufacturer Part Number: UFT43



Manufacturer	PANASONIC
MPN / Reference	UFT43
Catalog number	UFT43
Category	Fiber - PANASONIC
Minimum order	1 unit
Document ID	EO-74FC3C6B38
Generated	2026-08-03

Product Overview

UFT43 FT-43 PANASONIC Fiber (thru-beam, bending radius R4, M4, 2m, IP67)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PANASONIC > Fiber - PANASONIC > STANDARD type optical fibers

Additional Product Information

Product Number FT-43
Part Number FT-43
Product Thru-beam type Fiber
Details Threaded Type Fiber
Product name Threaded Type Fiber
Item Specifications
Product Number FT-43
Part Number FT-43
Sensing mode Thru-beam type
Fiber type Threaded type
Fiber head dia. M4
Fiber head length 15 mm
With sleeve No
Beam direction Top-view
Beam axis dia./ Spot diameter dia. 1.5 mm

Beam axis accuracy : Beam axis position 150 micro m
Beam axis accuracy : Beam axis Inclination plus or minus 2 degrees
Fiber cable length 2 m
Allowable bending radius R4 mm
Free-cut Available
Mounting lens Available
Applicable lens FX-LE1,FX-LE2,FX-SV1
Mounting protective tube FTP-500,FTP-1000,FTP-1500
Application General-purpose
Environmental resistance : Protection IP67
Environmental resistance : Ambient temperature MAX 80 degrees
Environmental resistance : Ambient temperature MIN -55 degrees
Sensing range(STD) 1,400 mm 55.118 in (FX-500 series)
Sensing range(HYPR) 3,600 mm 141.732 in (FX-500 series)
Sensing range(U-LG) 2,800 mm 110.236 in (FX-500 series)
Sensing range(LONG) 2,100 mm 82.677 in (FX-500 series)
Sensing range(FAST) 770 mm 30.315 in (FX-500 series)
Sensing range(H-SP) 240 mm 9.449 in (FX-500 series)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PANASONIC / UFT43 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.