

INDUSTRIAL COMPONENT DATA

UFX101PCC2 FX101PCC2 FX-101P-CC2 PANASONIC Fiber amplifier, Standard type, PNP, display, connector type, 2m ..

Brand: PANASONIC | Manufacturer Part Number: UFX101PCC2



Manufacturer	PANASONIC
MPN / Reference	UFX101PCC2
Catalog number	UFX101PCC2
Category	Fiber - PANASONIC
Minimum order	1 unit
Document ID	EO-73A6A1A697
Generated	2026-08-02

Product Overview

UFX101PCC2 FX101PCC2 FX-101P-CC2 PANASONIC Fiber amplifier, Standard type, PNP, display, connector type, 2m ..

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PANASONIC > Fiber - PANASONIC > FX100 preset fiber sensors

Additional Product Information

Product Number FX-101P-CC2

Part Number FX-101P-CC2

Product Digital Fiber Sensor

Details Standard type [Cable set]

Product name Digital Fiber Sensor FX-100

Item Specifications

Product Number FX-101P-CC2

Part Number FX-101P-CC2

CE marking directive compliance EMC Directive, RoHS Directive

Supply voltage 12 to 24 V DC plus or minus 10 % Ripple P-P 10 % or less

Power consumption Normal operation: 720 mW or less (Current consumption 30 mA or less at 24 V supply voltage)

ECO mode: 600 mW or less (Current consumption 25 mA or less at 24 V supply voltage)

Output PNP open-collector transistor

- Maximum source current: 100 mA

- Applied voltage: 30 V DC or less (between output and +V)

- Residual voltage: 1.5 V or less (at 100 mA source current)
Output: Output operation Selectable either Light-ON or Dark-ON, at SET mode
Output: Short-circuit protection Incorporated
External input PNP non-contact input
- Signal condition
High: +4 V to +V DC (Sink current 0.5 to 3 mA)
Low: 0 to +0.6 V DC or Open
- Input impedance: 10 kOhm approx.
Response time Emission frequency 0: 250 micro s or less (factory default setting)
Emission frequency 1: 450 micro s or less
Emission frequency 2: 500 micro s or less
Emission frequency 3: 600 micro s or less
Sensitivity setting 2-point teaching / Limit teaching / Full-auto teaching
Operation indicator Orange LED (lights up when the output is ON)
Digital display 4 digits (green) + 4 digits (red) LCD display
Fine sensitivity adjustment function Incorporated
Timer fun...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PANASONIC / UFX101PCC2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.