

INDUSTRIAL COMPONENT DATA

ULS401P LS401P LS-401P PANASONIC Laser Amplifier (with display), connector type, 2 outputs PNP

Brand: PANASONIC | Manufacturer Part Number: ULS401P



Manufacturer	PANASONIC
MPN / Reference	ULS401P
Catalog number	ULS401P
Category	Digital laser - PANASONIC
Minimum order	1 unit
Document ID	EO-B9D043181B
Generated	2026-08-03

Product Overview

ULS401P LS401P LS-401P PANASONIC Laser Amplifier (with display), connector type, 2 outputs PNP

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PANASONIC > Digital laser - PANASONIC > LS high precision Laser Sensor

Additional Product Information

Product Number LS-401P

Part Number LS-401P

Product Digital Laser Sensor

Details Amplifier (Connector type)

Product name Digital Laser Sensor LS-400

Item Specifications

Product Number LS-401P

Part Number LS-401P

Operation indicator Orange LED (lights up when output 1 and output 2 are ON)

Laser emission indicator Green LED (lights up during laser emission)

Ambient temperature -10 to +55 °C+14 to +131 °F(If 4 to 7 units are mounted close together: -10 to +50 °C+14 to +122 °F, if 8 to 16 units are mounted close together: -10 to +45 °C+14 to +113 °F)

(No dew condensation or icing allowed),

Storage: -20 to +70 °C-4 to +158 °F

Ambient humidity 35 to 85 % RH, Storage: 35 to 85 % RH

Voltage withstandability 1,000 V AC for one min.

between all supply terminals connected together and enclosure

Insulation resistance 20 MOhm , or more, with 250 V DC megger between all supply terminals connected together and enclosure

Vibration resistance 10 to 150 Hz frequency, 0.75 mm0.030 indouble amplitude in X, Y and Z directions for two hours each

Shock resistance 98 m/s²acceleration (10 G approx.) in X, Y and Z directions five times each

Material Enclosure: Heat-resistant ABS

Transparent cover: Polycarbonate

Push button switch: Acrylic

Jog switch: ABS

Cable -

(Note) The cable is not supplied as an accessory. Be sure to use the optional quick-connection cables given below.

Main cable (4-core): CN-74-C1 (cable length 1 m3.281 ft), CN-74-C2 (cable length 2 m6.562 ft), CN-74-C5 (cable length 5 m16.404 ft)

Sub....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PANASONIC / ULS401P with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.