INDUSTRIAL COMPONENT DATA

UMK-32 RM/MR-G24/1/YCS 2969055 PHOENIX CONTACT Active module

Brand: PHOENIX CONTACT | Manufacturer Part Number: UMK-32 RM/MR-G24/1/YCS



Manufacturer	PHOENIX CONTACT
MPN / Reference	UMK-32 RM/MR-G24/1/YCS
Catalog number	2969055
Category	Interface module
Minimum order	1 Pcs
Document ID	EO-8394B4F1A3
Generated	2026-11-18

Product Overview

Active module
32-channel relay module (1 open contact, 250 V AC/3 A) with screw connection. The module is activated via a 50-pole system connector and is suitable for Yokogawa ADV 551 and ADV 561 card.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

Key Commercial Data
Orderkey 2969055
Packing unit 1 pc
Note Made to Order (non-returnable)
Catalog page Page 226 (IF-2009)
GTIN 4046356163699
Weight per Piece (excluding packing) 411.800 g
Custom tariff number 85364190
Country of origin DE (Germany)
Note
Utilization restriction EMC: class A product, see manufacturer's declaration in the download area
Dimensions
Width 202 mm

Height 90 mm
Depth 58 mm
Ambient conditions
Ambient temperature (operation) -20 °C ... 50 °C
Ambient temperature (storage/transport) -20 °C ... 70 °C
Input data
Nominal input voltage UN 24 V DC
Input voltage range in reference to UN 0.9 ... 1.1
Typical input current at UN 6.5 mA (per channel)
Type of protection Free running
Protective circuit/component Damping diode
Type of protection Reverse polarity protection
Protective circuit/component Polarity protection diode
Operating voltage display Green LED
Status display/channel Yellow LED
Output data
Contact type 1 N/O contact
Maximum switching voltage 250 V AC
125 V DC
Minimum switching voltage 5 V AC/DC
Limiting continuous current 3 A
Maximum inrush current 2 A (Supply, (P1+, P2+), pluggable fuse (IEC 127-2, 5X20, 2A))
Min. switching current 10 mA
Interrupting rating (ohmic load) max. 72 W (at 24 V DC)
60 W (at 48 V DC)
50 W (at 60 V DC)
50 W (at 110 V DC)
750 VA (for 250 V AC)
Error detection (line break / short-circuit) no
General
No. of channels 32
Compatible components Miniature relay, REL-MR-G 24/1
With components yes
Degree of protection IP00
Mounting...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UMK-32 RM/MR-G24/1/YCS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.