INDUSTRIAL COMPONENT DATA

FLKM-PA-D37/HW/AN/C300 2900622 PHOENIX CONTACT Front adapters

Brand: PHOENIX CONTACT | Manufacturer Part Number: FLKM-PA-D37/HW/AN/C300



Manufacturer	PHOENIX CONTACT
MPN / Reference	FLKM-PA-D37/HW/AN/C300
Catalog number	2900622
Category	Accessories/spare parts for controls
Minimum order	1 Pcs
Document ID	EO-C1CA5B8A6D
Generated	2026-11-19

Product Overview

Front adapters
VARIOFACE Front Adapter, for Honeywell C300, C I/O Series, 1 x 16 Channel Max Connection (37-Pin D-SUB Plug-in Connector)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

Key Commercial Data
Orderkey 2900622
Packing unit 1 pc
Catalog page Page 486 (C-5-2017)
GTIN 4046356518208
Weight per Piece (excluding packing) 102.000 g
Custom tariff number 85366990
Country of origin DE (Germany)
Ambient conditions
Ambient temperature (operation) -20 °C ... 50 °C
Ambient temperature (storage/transport) -20 °C ... 70 °C
General
Max. permissible operating voltage 25 V AC

50 V DC
Max. permissible current 1 A (per path)
Mounting position any
Degree of protection IP00
Connection data 1
Connection name Field level
Connection method D-SUB pin strip
Number of connections 1
Number of positions 37
Connection data 2
Connection name Supply
Connection method Spring-cage connection
Conductor cross section solid 0.2 mm² ... 4 mm²
Conductor cross section flexible 0.2 mm² ... 2.5 mm²
Conductor cross section AWG 24 ... 12
Supported controller
Controller HONEYWELL Experion PKS C300/C-Series
- suitable I/O card TAIX01 (non-redundant)
TAIX11 (redundant)
TAIX51 (non-redundant)
TAIX61 (redundant)
TAIN01 (non-redundant)
TAIN11 (redundant)
TAOX01 (non-redundant)
TAOX11 (redundant)
Standards and Regulations
Standards/regulations DIN EN 50178
IEC 60664
Rated insulation voltage 63 V
Rated surge voltage 0.6 kV (Functional insulation)
Degree of pollution 2
Overvoltage category II
Environmental Product Compliance
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to tab “Downloads”, Category “Manufacturer's declaration”
Classifications
eCl@ss 5...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FLKM-PA-D37/HW/AN/C300 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.