INDUSTRIAL COMPONENT DATA

SAC-ASI-J-Y-B-PUR-2,0-OE 1407581 PHOENIX CONTACT Distributor

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-ASI-J-Y-B-PUR-2,0-OE



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-ASI-J-Y-B-PUR-2,0-OE
Catalog number	1407581
Category	Sensor actuator adapter
Minimum order	1 Pcs
Document ID	EO-11A141D8A3
Generated	2026-11-19

Product Overview

Distributor
Actuator and sensor interface splitter in high degree of protection, for a branch from two flat cables to 2.0 m PUR round cable with free cable end

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Key Commercial Data
Orderkey 1407581
Packing unit 1 pc
Catalog page Page 439 (C-2-2017)
GTIN 4046356780018
Weight per Piece (excluding packing) 97.000 g
Custom tariff number 85444290
Country of origin VN (Vietnam)
Dimensions
Length of cable 2 m
Ambient conditions
Degree of protection IP65
IP67

Ambient temperature (operation) -25 °C ... 75 °C
-25 °C ... 80 °C (cable, flexible installation)
-40 °C ... 80 °C (cable, fixed installation)
Ambient temperature (storage/transport) -25 °C ... 85 °C
General data
Rated current at 40°C 4 A
Rated voltage <= 32 V DC
Number of positions 4
Overvoltage category III
Degree of pollution 3
Connection method AS-i penetration technique
Characteristics head 1
Head type Load center lateral AS-i Screw locking
No. of positions (pin connector pattern) 4
Material (component) CuSn (Contact)
Ni/Au (Contact surface)
PBT (Contact carriers)
PBT (Housing)
Stainless steel (Screw connection)
Torque 1.65 Nm (Locking screw)
Characteristics head 2
Head type free cable end
Color black
Cable
Cable type PUR halogen-free black
Cable type (abbreviation) PUR
UL AWM style 20549 / 10493
Conductor cross section 4x 0.34 mm² (Signal line)
AWG signal line 22
Conductor structure signal line 42x 0.10 mm
Core diameter including insulation 1.25 mm ±0.05 mm
Wire colors brown, white, blue, black
Overall twist 4 wires, twisted
External sheath, color black
External cable diameter D 4.3 mm ±0.2 mm
Outer sheath, material PUR
Material conductor insulation PP
Conductor material Bare Cu li...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-ASI-J-Y-B-PUR-2,0-OE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.