INDUSTRIAL COMPONENT DATA

NBC-R4RC/2,0-93E/R4RC 1408942 PHOENIX CONTACT Network cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: NBC-R4RC/2,0-93E/R4RC



Manufacturer	PHOENIX CONTACT
MPN / Reference	NBC-R4RC/2,0-93E/R4RC
Catalog number	1408942
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-F90C8DEFB4
Generated	2026-11-19

Product Overview

Network cable
Ready-made Ethernet cable, CAT5e, shielded, 2 pairs, flexible AWG 26 (7 wires), RAL 5021 (aqua blue), RJ45/IP67 male connector push pull metal housing in RJ45/IP67 male push pull metal housing, Line, length 2 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data
Orderkey 1408942
Packing unit 1 pc
Note Made to Order (non-returnable)
Catalog page Page 402 (C-2-2017)
GTIN 4046356856713
Weight per Piece (excluding packing) 227.000 g
Custom tariff number 85444210
Country of origin PL (Poland)
Dimensions
Length of cable 2.00 m
Ambient conditions
Degree of protection IP67 (RJ45 connector)

Ambient temperature (operation) -40 °C ... 70 °C (RJ45 connector)
General data
Rated current at 40°C 1 A
Rated voltage 50 V
Number of positions 4
Standards/regulations IEC PAS 61076-3-117
Degree of pollution 2
Alternative short product description Ethernet cable
Locking type Push Pull
Rated voltage (III/3) 72 V (DC)
Characteristics head 1
Color silver
Material (component) CuSn (Contact)
Ni/Au (Contact surface)
PC (Contact carriers)
Zinc die-cast, nickel-plated (Housing)
Insertion/withdrawal cycles >= 750
Ambient temperature (operation) -40 °C ... 70 °C
Characteristics head 2
Color silver
Material (component) CuSn (Contact)
Ni/Au (Contact surface)
PC (Contact carriers)
Zinc die-cast, nickel-plated (Housing)
Insertion/withdrawal cycles >= 750
Ambient temperature (operation) -40 °C ... 70 °C
Standards and Regulations
Standards/regulations IEC PAS 61076-3-117
Flammability rating according to UL 94 V2
Cable
Cable type PUR ETHERNET 2x2 FLEX
Cable type (abbreviation) 93E
UL AWM style 20963 (80°C/30 V)
Signal type/category Ethernet CAT5 (IEC 11801), 100 Mbps
Cable structure 2x2xAWG26/7; SF/UTP
Conductor cross section 2x 2x 0.14 mm²
AWG signal li...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / NBC-R4RC/2,0-93E/R4RC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.